

	MWH Americas, Inc. 335 Phoenixville Pike Malvern, Pennsylvania 19355	Boring ID: 1K Page 1 of 4	DC53-97
	Project Name: from URS gINT database urs_excel_3_19_06.gpj Location: Delaware City, DE Project Number: Date Started: 10/23/2002 Date Finished: 10/23/2002 Drilling Method: Hollow Stem Auger Sampling Method: State Permit Number: NA	Boring Location: Delaware City Refinery - Crude South Drilling Company: Walton Corporation (Gary Truver) Ground Elevation (ft/msl): 32.6 Total Depth (ft): 109.0' Boring Diameter (in): " Water Level During Drilling (ft/bgs): Weather Conditions: Logged By: Vince Piazza	

Depth (feet)	Blow Counts	Recovery (inches)	PID (ppm)	Sample ID	Sample Interval	USCS	Lithology	Lithologic Description	Well Diagram	Remarks
0								0' - 0.5' Topsoil		
0.5						SW-SM		0.5' - 67' orange-brown, fine to coarse SAND and SILT with interbedded GRAVEL layers		
5										
10										
15										
20										
25										
30										



Depth (feet)	Blow Counts	Recovery (inches)	PID (ppm)	Sample ID	Sample Interval	USCS	Lithology	Lithologic Description	Well Diagram	Remarks
30										
35										
40										
45										
50										
55										
60										
65										

DC53-997



MWH Americas, Inc.
335 Phoenixville Pike
Malvern, Pennsylvania 19355

Boring ID: 1K

Page 3 of 4

Depth (feet)	Blow Counts	Recovery (inches)	PID (ppm)	Sample ID	Sample Interval	USCS	Lithology	Lithologic Description	Well Diagram	Remarks
70						SW-SM		67' - 106.5' orange-brown, fine to coarse SAND and SILT with interbedded GRAVEL layers		
75										
80										
85										
90										
95										
100										



Depth (feet)	Blow Counts	Recovery (inches)	PID (ppm)	Sample ID	Sample Interval	USCS	Lithology	Lithologic Description	Well Diagram	Remarks
105										
						CL		106.5' - 109' dark gray, micaceous CLAY + trace very fine SAND		
110										
115										
120										
125										
130										
135										