


GWSB

Ec12-33

	MWH Americas, Inc. 335 Phoenixville Pike Malvern, Pennsylvania 19355	<b>Boring ID: 1A</b> Page 1 of 3
	<b>Project Name:</b> from URS gINT database urs_excel_3_19_06.gpj <b>Location:</b> Delaware City, DE <b>Project Number:</b> <b>Date Started:</b> 10/17/2002 <b>Date Finished:</b> 10/17/2002 <b>Drilling Method:</b> Hollow Stem Auger <b>Sampling Method:</b> <b>State Permit Number:</b> NA	<b>Boring Location:</b> Delaware City Refinery - S. Process <b>Drilling Company:</b> Walton Corporation (Gary Truver) <b>Ground Elevation (ft/msl):</b> 58.5 <b>Total Depth (ft):</b> 80.0' <b>Boring Diameter (in):</b> " <b>Water Level During Drilling (ft/bgs):</b> <b>Weather Conditions:</b> <b>Logged By:</b> Vince Piazza

Depth (feet)	Blow Counts	Recovery (inches)	PID (ppm)	Sample ID	Sample Interval	USCS	Lithology	Lithologic Description	Well Diagram	Remarks
0							TOPSOIL SW	0' - 0.5' Topsoil		
0.5								0.5' - 67' orange-brown, fine to medium SAND with interbedded SILT, CLAY and GRAVEL layers		
5										
10										
15										
20										
25										
30										



**MWH**

MWH Americas, Inc.  
335 Phoenixville Pike  
Malvern, Pennsylvania 19355

**Boring ID: 1A**

Page 2 of 3

Depth (feet)	Blow Counts	Recovery (inches)	PID (ppm)	Sample ID	Sample Interval	USCS	Lithology	Lithologic Description	Well Diagram	Remarks
30										
35										
40										
45										
50										
55										
60										
65										



Depth (feet)	Blow Counts	Recovery (inches)	PID (ppm)	Sample ID	Sample Interval	USCS	Lithology	Lithologic Description	Well Diagram	Remarks
70						SW		67' - 79' orange-brown, fine to medium SAND with interbedded SILT, CLAY and GRAVEL layers		
75										
80						CL		79' - 80' dark gray, silty, micaceous CLAY + trace fine SAND		
85										
90										
95										
100										