


EC 12-50

 <b>MWH</b> MWH Americas, Inc. 335 Phoenixville Pike Malvern, Pennsylvania 19355	<b>Boring ID: 2B</b> Page 1 of 3	
	<b>Project Name:</b> from URS gINT database urs_excel_3_19_06.gpj <b>Location:</b> Delaware City, DE <b>Project Number:</b> <b>Date Started:</b> 10/24/2002 <b>Date Finished:</b> 10/24/2002 <b>Drilling Method:</b> Hollow Stem Auger <b>Sampling Method:</b> <b>State Permit Number:</b> NA	<b>Boring Location:</b> Delaware City Refinery - Soy Field <b>Drilling Company:</b> Walton Corporation (Gary Truver) <b>Ground Elevation (ft/msl):</b> 56.8 <b>Total Depth (ft):</b> 74.0' <b>Boring Diameter (in):</b> " <b>Water Level During Drilling (ft/bgs):</b> <b>Weather Conditions:</b> <b>Logged By:</b> Vince Piazza

Depth (feet)	Blow Counts	Recovery (inches)	PID (ppm)	Sample ID	Sample Interval	USCS	Lithology	Lithologic Description	Well Diagram	Remarks
0							TOPSOIL	0' - 1' Topsoil		
1						SW-SM		1' - 13.5' brown, fine to medium SAND and SILT + trace fine, rounded GRAVEL		
5										
10										
13.5						SW-SM		13.5' - 60' orange-brown, fine to medium SAND and SILT + trace GRAVEL		
15										
20										
25										
30										



Depth (feet)	Blow Counts	Recovery (inches)	PID (ppm)	Sample ID	Sample Interval	USCS	Lithology	Lithologic Description	Well Diagram	Remarks
30										
35										
40										
45										
50										
55										
60						SW-SM		60' - 67' brown, fine to medium SAND and little SILT + trace fine, rounded GRAVEL		
65										



**MWH**

MWH Americas, Inc.  
335 Phoenixville Pike  
Malvern, Pennsylvania 19355

**Boring ID: 2B**

Page 3 of 3

Depth (feet)	Blow Counts	Recovery (inches)	PID (ppm)	Sample ID	Sample Interval	USCS	Lithology	Lithologic Description	Well Diagram	Remarks
70						SW-SM		67' - 72.5' brown, fine to medium SAND and little SILT + trace fine, rounded GRAVEL		
75						CL		72.5' - 74' dark gray CLAY and little mica + trace very fine SAND		
80										
85										
90										
95										
100										