A.C. SCHULTES OF MARYLAND, INC. 24-26 SOUTH RIVER ROAD EDGEWATER, MARYLAND 21037

Water Well Contractors

CUSTOMER: Artesian					JOB _	H3918
ADDRESS: Corner of Windsong and Rt. G					DATE	8/29/01
LOCATION: West of Clayton, DE				•	PERMIT NO.	
FEET FROM SURF 0 TO			ACE		WELL ŁOG	
GROUND		0-1		Top soil		
1		1-57		Medium to course sand with some clay		
TOTAL DEPTH-FT.		57-85		Course sand		
		85-161		Gray and brown clay with fine black sand		
		161-180		Silt and fine black sand with clay		
		180-204		Gray clay with fine black sand (very slow)		
		205-269		Course to fine sand		
		269-282		Medium to fine sand with some clay		
		282-390		Hard layers of cemented sand and shell with some clay (very slow)		
		390-452		Fine to medium sand with some clay		
		452-537		Medium to fine sand		
	CASING	537-566		Fine to medium sand with gray clay		
		566-569		Hard layer of cemented sand and shell		
		569-641		Fine sand with silt and clay		
		641-650		Gray clay		
		650-676		Silt and fine sand		
	2 11	676-695		Fine sand with silt and clay		
	Z Z Z Z Z Z Z Z					
1						
WELL NO. OBS DIAMETE			DIAMETER (OF WELL 2"	DEPT. OF WELL	480
HRS. PUMPED 4 SLOT SIZE			SLOT SIZE	.020	TYPE OF CASING Steel	
CAPACITY G. P. M. 40 DRILLING			DRILLING M	CHINE NO. D-8 LENGTH OF CASING 462		
STATIC LEVEL 41 D			DRILLER Watson		DISTANCE TO TOP	OF SCREEN 460
PUMPING LEVEL 81			GRAVEL Morie #1		TYPE SCREEN Stainless Steel	
			BAGS OF	CEMEN <u>T 260</u>	SIZE OF SCREEN 2" P.S.	
PUMPED WITH Air DA			DATE WELL	COMPLETED 10/20/01		
DEPTH OF GROUT 0-400 DRILLE				HELPER Melson		
DEPTH GRAVEL PACKED 400-520					WELL DRILL	ER'S SIGNATURE