MAIL TO:

PLEASE PRINT

WATER SUPPLY BRANCH
DIVISION OF ENVIRONMENTAL CONTROL
P.O. BOX 1401
DOVER, DELAWARE 19903

STATE OF DELAWARE DEPARTMENT OF NATURAL RESOURCES AND ENVIRONMENTAL CONTROL

WELL COMPLETION REPORT MUST BE RETURNED 30 DAYS AFTER CONSTRUCTION DATE

WELL COMPLETION REPORT

PERMIT NOLOCAL ID		TYPE OF PERMANENT PUMP INSTALLED:	
OWNER		PUMP MANUFACTUREN/A	
		RATED CAPACITY (GPM)	
CONSTRUCTION DATE 7-13-89		PUMP INTAKE SETTING FT.	BELOW CRADE
PURPOSE: TEST	PERMANENT	THE COMPLETED V	WELL IS?
USE: DOMESTIC SE AGRICULTURAL		A. AT LEAST 15' FROM ANY FOUNDATION	YES NO
COMMERCIAL INDUSTRIAL		B. AT LEAST 50' FROM ANY SEPTIC TANK	-, -
☐ IRRIGATION	□ PUBLIC	C. AT LEAST 10' FROM TOWN SEWER LIN	
☐ OBSERVATION ☐ DEWATERING		D. AT LEAST 100' FROM THE NEAREST EDGE	
☐ HEAT PUMP RECHARGE ☐ HEAT PUMP SUPPLY		OF ANY TILE FIELD	DGE 44 LJ
xxx OTHER (Specify) Lawn Trrigation		THE NEAREST NEIGHBORS (CIRCLE ONE)	
IS THIS A REPLACEMENT WELL? YES WORKEN		SEPTIC THE FIEDD CESSPOOL OR PRIVY	
ABANDONMENT DATE FOR OLD WELL7-8-39		IS 100 FROM COMPLETED WELL.	
ABANDONMENT METHODclay		IS COMPLETED WELL LOCATED AS SHOWN	
		ON APPLICATION FORM?	/
DRILLING METHOD		ON APPLICATION FORM? IF NO, DESCRIBE LOCATION CHANGE OR OTHER COMMENTS.	
☐ AUGERED ☐ BORED ☐ CABLE TOOL		ITO, DESCRIBE LOCATION CHANGE OR	OTHER COMMENTS.
	ETTED AIR ROTARY	0. 35 60	
	REVERSE WASHED	Pb54-03	
OTHER (Specify)		1 10	\sim
TOTAL DEPTH DRILLED	45-		
- · · ·		3 3 3	1 4
CASING SEQUENCE			
	INNER OUTER	1147	:
CASING TOP	2'	1 -0-	~ 98 9
CASING BOTTOM 4	0		
CASING DIAMETER	4"		
CASING MATERIAL P	vc	WATER	SUPPL
SCREEN SEQUENCE		3 3 3 3 - 1	
	INNER OUTER		
SCREEN TOP L.	40		
SCREEN BUILDIN	45	DRILLERS LOG DESCRIPTION TOP OF STR	ATA BOTTOM OF STRATA
SCREEN DIAMPTER L	4"		
SCREEN MATERIAL P	VC	Top Soil 0	1
	WRITTEN APPROVAL FOR SCREENING/ GRAVEL PACKING MORE THAN ONE AQU- IFER MUST BE OBTAINED FROM DNREC.	Brown Sand 1	7,5
GROUT TYPE: CEMENT 🗀	BENTONITE CLAY 🖾	Gray Clay w/#3 Stone 7.5	15
OTHER:	0	<u>Lighe tan coarse sand 15</u>	30
FROM U TO 4U FEET NON-GROUT BACKFILL OF WELL ANNULUS		Light tan fine sand 30	40
		Light tan fine sand 40	50
GRAVEL PACK: TYPE	то feeт #2	Light tan fine same 40	20
FROM 40 TO 50			
STATIC WATER LEVEL: DATE			
9 8 FT. (Below, above) GROUND SURFACE			
PUMPING WATER LEVEL: 15 FT. BELOW GRADE			
AFTER 1/2 HOURS AT.	CPM.		
WELL HEAD COMPLETION:			
		SUPPLEMENTAL DRILLERS LOG ATTACHED YES D NO D	
TYPE: PITLESS ADAPTOR MO		PAGE 1 OFPAGES	
UZ INCHES ABOVE GRADE.		COMPANY NAME Award 10.16 +7	
TO INCHES ABOVE GRADE.		SIGNATURE OF DRILLER IN CHARGE: DATE	
		Al MERGY	
, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			