

Delmarva Drilling Co., Inc. PC34-5

P. O. BOX 188

BRIDGEVILLE, DELAWARE 19933

Water Well Contractors

CUSTOMER Town of Blades JOB 4250
 ADDRESS Blades, De. DATE _____
 LOCATION 90' 7" SE of well #2, and 125' E. of road

	FEET FROM GROUND SURFACE 0 TO.....	WELL LOG
GROUND	0 - 1	top soil
<div style="display: flex; align-items: center;"> <div style="margin-right: 10px;"> <p style="writing-mode: vertical-rl; transform: rotate(180deg);">95'</p> <p style="writing-mode: vertical-rl; transform: rotate(180deg);">TOTAL DEPTH - FT.</p> </div> <div style="border: 1px solid black; padding: 5px; text-align: center;"> <p style="writing-mode: vertical-rl; transform: rotate(180deg);">65'</p> <p>← CASING →</p> </div> </div>	1 - 6	fine to med. sand
	6 - 21	gray clay w/fine sand
	21 - 43	fine to med. brown sand
	43 - 50	fine to coarse tan sand w/gravel
	50 - 53	gravel
	53 - 97	fine to coarse tan sand w/gravel
	97 - 120	blue clay w/fine sand layers
	SCREEN	50'

WELL NO. <u>2</u>	DIAMETER OF WELL <u>10"</u>	DEPT. OF WELL <u>95'</u>
HRS. PUMPED <u>3 1/2</u>	SLOT SIZE <u>.045</u>	TYPE OF CASING <u>steel</u>
CAPACITY G.P.M. <u>35</u>	DRILLING MACHINE NO. <u>D3</u>	LENGTH OF CASING <u>65'</u>
STATIC LEVEL <u>17' 5"</u>	DRILLER <u>Kelley & Cowgill</u>	DISTANCE TO TOP OF SCREEN <u>65-95'</u>
PUMPING LEVEL <u>19' 5"</u>	GRAVEL <u>2 & 3</u>	TYPE SCREEN <u>Stainless steel</u>
SPECIFIC CAPACITY <u>17</u>	BAGS OF CEMENT <u>50</u>	SIZE OF SCREEN <u>8"</u>
PUMPED WITH <u>air pumper</u>	DATE WELL COMPLETED <u>11-3-78</u>	
DEPTH OF CEMENT GROUT <u>0-45'</u>	DRILLER'S HELPER <u>Moore & Dunn</u>	Kelley & Cowgill
DEPTH GRAVEL PACKED <u>45-95'</u>		WELL DRILLER'S SIGNATURE