WALTON CORPORATION Pg 55-15
Drilling Contra
P. O. BOX 1097, NEWARK, DELAWARE 19711

BORING LOG

A. Townsends Inc. - Spray Irrigation Facility ... PROJECT NO. 130-2
Millsboro, DE ... SUPERVISOR

BORING NO.	DRILLER	DATE
Temp. Piezometer C TW-C	G. Truver	10-31-78
WEATHER	**SURFACE ELEVATION**	**DATUM**
Warm	27.2 ft.	USGS (approx. @ 1 ft.±)

Sample No.	Sample Depth - Feet From	Sample Depth - Feet To	Depth Strata Feet From	Depth Strata Feet To	Driller's Description of Materials	*Blows A		
1	0	1.5	0	1.5	Dk. Brn. F Sand w/Tr. Silt	2	2	3
2	1.5	3.0	1.5		Lg. Brn. F Sand w/Tr. Silt	2	2	2
3	4.0	5.5			Same	3	4	5
4	6.0	7.5		7.0	Same	5	6	8
	-		7.0	8.0	Brn. F Sand w/Some Silt & Tr.			
					Gravel			
5	9.0	10.5	8.0	12.5	Lg. Brn. F Sand w/Tr. Silt	10	10	9
6	14.0	15.5	12.5	18.0	Orange Brn. F/C Sand w/Some Silt	11	13	13
7	19.0	20.5	18.0	20.0	Orange Brn. F Sand w/Tr. Silt	10	10	10
			20.0		Brownish White F Sand w/Tr. Silt			
8	24.0	25.5		27.0	Brownish White F/C Sand w/Some	14	18	13
					Silt & Gravel (Moist)			
9	29.0	30.5	27.0	31.0	Brownish White Silty F Sand	12	13	10
					w/Gravel Layer			

*A Number of blows of 140 lb. hammer dropped 30 in. required to drive 2 in. split-spoon sampler for each of three 6 in. increments.

* B Number of blows of 300 lb. hammer dropped 18 in. required to drive ..... in. casing 12 inches.

REMARKS: .....Wet on Spoon @ 26.0.....
.....W/L @ completion 28.5.....
.....
.....

GROUND WATER

BLOWS ON CASING B
0- 1
1- 2
2- 3
3- 4
4- 5
5- 6
6- 7
7- 8
8- 9
9-10
10-11
11-12
12-13
13-14
14-15
15-16
16-17
17-18
18-19
19-20
20-21
21-22
22-23
23-24
24-25
25-26
26-27
27-28
28-29
29-30
30-31
31-32
32-33
33-34
34-35
35-36
36-37
37-38
38-39
39-40
40-41
41-42
42-43
43-44
44-45
45-46
46-47
47-48
48-49
49-50
50-51
51-52
52-53
53-54
54-55
55-56
56-57
57-58
58-59
59-60
60-61