STATE OF DELAWARE

DEPARTMENT OF NATURAL RESOURCES AND ENVIRONMENTAL CONTROL

WELL COMPLETION REPORT MUST BE RETURNED 30 DAYS AFTER CONSTRUCTION DATE

Ã,

JUPPLY BRANCH
JION OF ENVIRONMENTAL CONTROL
∠O, BOX 1401
20VED DELAWADE 10003

PLEASE PRINT		WELL COMPL	ETION REPORT		
PERMIT NO. 89527 LOCAL ID			TYPE OF PERMANENT PUMP INSTALLED:		
Tunnell.	Companies.	L.P.			
OWNER Tunnell Companies, L.P. P.O. Box 368, Millsboro, DE 19966			PUMP MANUFACTURE	/	
CONSTRUCTION DATE	03/30/93	00.00, 00 17700	RATED CAPACITY (GPM)	/	
PURPOSE: TEST			PUMP INTAKE SETTING		
FUNFUSE. LI IESI		⊠ PERMANENT	I THE COM	PLETED WELI	LIS: YES NO
USE: DOMESTIC		☐ AGRICULTURAL	A. AT LEAST 15' FROM ANY FOU	INDATION	7ES NO
□ COMMERCIAL		☐ INDUSTRIAL	B. AT LEAST 50' FROM ANY SEPTIC TANK		_
□ IRRIGATION		Ø PUBLIC	C. AT LEAST 10' FROM TOWN SEWER LINE 🔯		
		☐ DEWATERING	D. AT LEAST 100' FROM THE NEAREST EDGE 🖾 🗆		
☐ HEAT PUMP RECHARGE ☐ HEAT PUMP SUPPLY		OF ANY TILE FIELD			
OTHER (Spe			THE NEAREST NE	GHBORS (CI	RCLE ONE)
IS THIS A REPLACEME	ENT WELL? YES	□ NO⊠	SEPTIC TILE FIELD CES		
ABANDONMENT DATE FOR OLD WELL			IS 100+ FROM COMPLETED	WELL.	
ABANDONMENT METHOD			IS COMPLETED WELL LOCATED AS SHOWN		
			ON APPLICATION FORM?		*
_	DRILLING ME		IF NO, DESCRIBE LOCATION C	HANGE OR OTH	IER COMMENTS.
□ AUGERED		CABLE TOOL	-		1
DRIVEN		☐ AIR ROTARY	RD 22c		1.
MUD ROTARY	□ REVERSE	☐ WASHED		N	— 3
OTHER (Specify) -	0 1/3		Į.	- 1	. (&)
TOTAL DEPTH DRILLE	U <u> </u>			1	L
	CASING SEQU	IENCE	** ** ** ** * * * *		8 2
	INNER	OUTER	* This was 800 ==	> 389'	
CASING TOP	+2'		Company of the medium product of the control of the	1	* This .
CASING BOTTOM	93			į	* 12
CASING DIAMETER	8"		The second secon	J.	
CASING MATERIAL	PVC				79
	SCREEN SEQ		1100 26 22		
	INNER O2'	OUTER	MALS	O(3)	21-11
SCREEN TOP	113'		Supplies to the section of the secti	11	21 11
SCREEN BOTTOM	12		QRIVIYA'S LOGITESCRIPTION	TOP OF STRATA	BOTTOM OF STRA
SCREEN DIAMETER	PVII		Top soil	0	1
SCREEN MATERIAL	WRITT	EN APPROVAL FOR SCREENING/	Brown clay	7	6
	IFER N	L PACKING MORE THAN ONE AQU- IUST BE OBTAINED FROM DNREC.	Jan fine to coarse	•	
GROUT TYPE: CEME	NT □ BENTONII	TE CLAV 🛱	Isana	6	17
OTHER:			Tan fine to coarse sand w/gravel	17	50
FROM			Tian filme to coarse [50	79
			sand		<u> </u>
			Gray clay	79	85
FROM 60 TO 114 FEET			Tan fine to coarse sand w/gravel	85	121
FROM <u>60</u> 1	ro <u>// 7</u> F	FET.	Samu w/ g/mvex.		
STATIC WATER LEVEL	L: DATE	700			
FT. Below abo					
PUMPING WATER LEVEL: 14 FT. BELOW GRADE AFTER HOURS AT GPM.					
WELL HEAD COM	MPI FTION:		SUPPLEMENTAL DRILLERS LO	OG ATTACHED	YES D NOWTH
WELL HEAD COMPLETION: TYPE: PITLESS ADAPTOR □			PAGE 1 OFPAGES	NO ALLAURED	ILU III HOMA
OTHER DE CAPP	ed:		COMPANY NAME _AMERIC	an Water u	Iell Systems.
AH INCHES ABOV	E GRADE.		SIGNATURE OF DRILLER IN C		
1.			Cabrin War, le		- •
			www a we fee	anon	