## MAIL TO:

PLEASE PRINT

WATER SUPPLY BRANCH DIVISION OF ENVIRONMENTAL CONTROL P.O. BOX 1401 DOVER, DELAWARE 19903

## STATE OF DELAWARE **DEPARTMENT OF NATURAL RESOURCES** AND ENVIRONMENTAL CONTROL

WELL COMPLETION REPORT MUST BE RETURNED 30 DAYS AFTER CONSTRUCTION DATE

## WELL

COMPLETION	REPORT	J.

1-4

PERMIT NO. 107837 LOCAL ID 319	TYPE OF PERMANENT PUMP INSTALLED:	
OWNER Yosoph Umstatter	PUMP MANUFACTURE	
	RATED CAPACITY (GPM)	
CONSTRUCTION DATE	PUMP INTAKE SETTING FT. BELOW GRADE	
PURPOSE:   TEST  PERMANENT	THE COMPLETED WELL IS?	
USE: DOMESTIC GAGRICULTURAL DINDUSTRIAL	A. AT LEAST 15' FROM ANY FOUNDATION  B. AT LEAST 50' FROM ANY SEPTIC TANK  ZY	
□ IRRIGATION □ PUBLIC	C. AT LEAST 10' FROM TOWN SEWER LINE	
☐ OBSERVATION ☐ DEWATERING	D. AT LEAST 100' FROM THE NEAREST EDGE	
☐ HEAT PUMP RECHARGE ☐ HEAT PUMP SUPPLY	OF ANY TILE FIELD	
☐ OTHER (Specify)	THE NEAREST NEIGHBORS (CIRCLE ONE)	
IS THIS A REPLACEMENT WELL? YES ₽ NO□	SEPTIC CILLETHELD CESSPOOL OR PRIVY	
ABANDONMENT DATE FOR OLD WELL	T DATE FOR OLD WELL 5-33-96 IS 1001 FROM COMPLETED WELL.	
ABANDONMENT METHOD	IS COMPLETED WELL LOCATED AS SHOWN	
· ·	ON APPLICATION FORM?	
DRILLING METHOD	IF NO, DESCRIBE LOCATION CHANGE OR OTHER COMMENTS.	
☐ AUGERED ☐ BORED ☐ CABLE TOOL	1	
☐ DRIVEN ☐ JETTED ☐ AIR ROTARY		
MUD ROTARY □ REVERSE □ WASHED		
OTHER (Specify)		
TOTAL DEPTH DRILLED 220	·	
CASING SEQUENCE		
INNER OUTER		
CASING TOP		
CASING BOTTOM		
CASING DIAMETER CASING MATERIAL PVC		
SCREEN SEQUENCE		
INNÉR OUTER	P; 51-07	
SCREEN TOP SCREEN BOTTOM 220	DRILLERS LOG DESCRIPTION TOP OF STRATA BOTTOM OF STRATA	
SCREEN DIAMETER		
SCREEN MATERIAL POPPER	Tout fill 0 3	
WRITTEN APPROVAL FOR SCREENING/ GRAVEL PACKING MORE THAN ONE AQU- IFER MUST BE OBTAINED FROM DNREC.	5et c 3 19	
IFER MUST BE OBTAINED FROM DNREC.	cle : 19 26	
GROUT TYPE: CEMENT D BENTONITE CLAY	1 80	
OTHER:	San frie Sy 26 70	
FROM O TO 210 FEET	Sent relation 70 150	
NON-GROUT BACKFILL OF WELL ANNULUS  TYPE FROM TO FEET	cla ( 150 190	
TYPE FROM TO FEET  GRAVEL PACK: TYPE FROM SAND	0 = 7	
FROM 210 TO 8.3. FEET	Suffer 87 120 200	
STATIC WATER LEVEL: DATE 5-23-96	Santhutner 8 200 220	
FT. (Below, above) GROUND SURFACE	-, , , ,	
PUMPING WATER LEVEL: 2FT. BELOW GRADE		
AFTER HOURS AT GPM.		
WELL HEAD COMPLETION:  TYPE: PITLESS ADAPTOR □	SUPPLEMENTAL DRILLERS LOG ATTACHED YES IN NO PAGE 1 OF PAGES	
OTHER I Tose Try to Tags  LINCHES ABOVE GRADE.	SIGNATURE OF DRILLER IN CHARGE: DATE  L'GULLUM 5/23/96	