

Handwritten notes:
 KDW
 to construct well products

TELEPHONE 302/337-8234

Delmarva Drilling Co., Inc. #33614

P. O. BOX 188

BRIDGEVILLE, DELAWARE 19933

QC A2-3 SHA

Water Well Contractors

CUSTOMER George J. Collins **RECEIVED** JOB 2622
 ADDRESS Laurel, Del. JUN 6 1975 DATE 3/6/75
 LOCATION DELAWARE GEOLOGICAL SURVEY

		FEET FROM GROUND SURFACE 0 TO.....	WELL LOG
GROUND	↑ TOTAL DEPTH - FT. 120' ↓	0-1	top soil
		1-6	fine to med. brown sand
		6-8	brown clay
		8-43	fine to med. brown sand w/50% gravel iron c
		43-111	fine to coarse tan sand w/50 % gravel
		111-121	fine to med. tan sand
		121-141	fine tan sand w/gray and white clay layers
		xxx	
←CASING→	80' ↓		pumped for 1 hr. 60 GPM
			pumping level 12' 2"
SCREEN	70' ↓		

WELL NO. <u>1</u>	DIAMETER OF WELL <u>4"</u>	DEPT. OF WELL <u>120 ft.</u>
HRS. PUMPED <u>1 1/2</u>	SLOT SIZE <u>.016</u>	TYPE OF CASING <u>PVC</u>
CAPACITY G.P.M. <u>60</u>	DRILLING MACHINE NO. <u>D-3</u>	LENGTH OF CASING <u>80</u>
STATIC LEVEL <u>9</u>	DRILLER <u>Ed Kelley</u>	DISTANCE TO TOP OF SCREEN <u>80-120</u> F.
PUMPING LEVEL <u>12' 2"</u>	GRAVEL <u>2</u>	TYPE SCREEN <u>PVC</u>
SPECIFIC CAPACITY <u>30</u>	BAGS OF CEMENT <u>clay seal</u>	SIZE OF SCREEN <u>4"</u>
PUMPED WITH <u>pumper</u>	DATE WELL COMPLETED <u>3/6/75</u>	
DEPTH OF CEMENT GROUT <u>clay seal</u>	DRILLER'S HELPER <u>B. Cowgill</u>	
DEPTH GRAVEL PACKED <u>70-120</u>		<u>Ed Kelley</u>