STATE OF DELAWARE **DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAYS**

| F.A. Project: | S.R. 26, Atlantic Avenue from Clarksville to Assawoman Canal | Boring No.: | RR#17 |
|----------------|--|--------------------|-----------|
| Contract: 24-1 | 12-10 | | 100 // 17 |

Boring Location: Sta. 31+75, 15' Rt. C.L.

Boring Surface Elev.:

Reference: Wt. of Casing Hammer:
Wt. of Sample Hammer: 140
Type of: D-Sampler: S-Sampler:
U-Sampler: Core Bit: Lbs. Lbs. O.D. O.D. 30

Average Fail: Average Fail: O.D. of Sampler: O.D. of Samp. Tube: O.D. of Samp. Tube: O.D. of Rock Core: Split-Barrel

Casing Size: 3 1/4" Hollow Stem Auger: From Depth of: From Depth of: To: To: Inches 0.0 6.0

Water Level Readings Date Depth of Hole **Depth of Casing** Depth of Water Elev. of Water

Pay Quantities: 2 1/2 in. Dia. Dry Sample Boring: No. of 2 in. Dia. Shelby Tubes: 2 1/2 in. Dia. Contin. Sample Boring: 8.0 Ft; Dia. U-Sample Boring: U-Samples: Ft. No. of: Ft.: Core Drilling in Rock: Ft.

Boring Contractor: Walton Corporation Driller: Dave Burt

Helpers: Jim Deal & Wayne Hurd

10:72-17

| Tiespers: Jilli Deal & Wayne Huld | | | | | | | | |
|-----------------------------------|-------------------|-----|-----------------|-------------------|--|-------------|---------|--|
| Depth (ft.) | Daily Progress | No. | Sample Depth | Blows/6" | Sample Description | Class./G.I. | Remarks | |
| 3 | | 1 | 2.0' 4.0' | 1222 | Moist very loose brown fine sand w/some coarse sand, trace of silt. 20" RECOVERY | A-3 | | |
| | | 2 | 4.0' | 2 2 3 4 | Moist loose brown fine to coarse sand w/ trace of silt. | A-3 | | |
| 6 | | 3 | 5.0' 6.0' | 2 5 | Wet loose brown fine sand w/some coarse sand and silt. | A-2-4(0) | | |
| | | 3A | 6.0° 7.0° | 3 4 | 24" RECOVERY Wet firm brownish gray clayey fine sandy silt w/trace of coarse sand and gravel. 12" RECOVERY 12" RECOVERY | A-4(1) | | |
| 9 | | 4 | 8.0' | 5 6 7 10 | Saturated stiff brownish gray silty clay w/ some fine sand, trace of coarse sand. | A-6(9) | | |
| | | | 10.0' | | 22" RECOVERY | | | |
| 12 | | | | | | | | |
| | | | | | | | | |
| 15 | · | | | | | | | |
| | | • | | | | | | |
| 18 | | | | | | | | |

Remarks:

| D. 1 1D | |
|--------------|-------------------|
| Reviewed By: | Soils Supervisor: |

KEY TO SYMBOLS

Symbol Description

Strata symbols

Sand

Silt

Low plasticity clay

Notes:

- 1. Exploratory borings were drilled on 5-4-2006 using a 3 1/4-inch diameter hollow stem auger.
- 2. No free water was encountered at the time of drilling or when re-checked the following day, unless recorded on 1st page.
- 3. Boring locations were taped from existing features and elevations extrapolated from survey unless otherwise reported.
- 2. These logs are subject to the limitations, conclusions, and recommendations in this report.
- 5. Results of tests conducted on samples recovered are reported on the logs.