## STATE OF DELAWARE **DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAYS**

F.A. Project:	S.R. 26, Atlantic Avenue from Clarksville to Assawoman Canal	Boring No.:	RB # 22
Contract: 24-	112-10		

Boring Location: Sta. 40+70, 10' Lt. C.L. **Boring Surface Elev.:** 

Reference: Wt. of Casing Hammer:
Wt. of Sample Hammer:
Type of:
D-Sampler:
S-Sampler:
U-Sampler: Average Fall: Average Fall: O.D. of Sampler: O.D. of Samp. Tube: O.D. of Samp. Tube: O.D. of Rock Core: Lbs. Lbs. O.D. Split-Barrel O.D. O.D. O.D. Core Bit:

Casing Size: 3 1/4"
Hollow Stem Auger: From Depth of: From Depth of: inches To: To: 0.0 6.0

Water Level Readings Date 5/10/2006 Time Depth of Hole Depth of Water 6.0' Depth of Casing Elev. of Water 11:00 a.m. 8.0 6.0 -6.0

Pay Quantitles: 2 1/2 in. Dia. Dry Sample Boring: No. of 2 in. Dia. Shelby Tubes: 2 1/2 in. Dia. Contin. Sample Boring: Dia. U-Sample Boring: U-Samples: 8.0 Ft.;

Ft. No. of: Fť.; Core Drilling in Rock: Ft.

Boring Contractor: Walton Corporation Driller: Dave Burt

Helpers: Jim Deal & Wayne Hurd (0:22-22

——————————————————————————————————————							
Depth (ft.)	Daily Progress	No.	Sample Depth	Blows/6"	Sample Description	Class./G.I.	Remarks
3		1	2.0' 4.0'	6	Wet medium dense brown fine sand w/ some silt and coarse sand.  6" RECOVERY	A-2-4(0)	
		2	4.0'	3 4 3 4	Wet loose brown fine sand w/some coarse sand and silt.	A-2-4(0)	
6		3 3A	5.5' \ 6.0'	2 2 3	Wet loose brown silty fine sand w/some	A-2-4(0)	
			6.0' 6.5' / 7.0'	3	Coarse sand.  20" RECOVERY  Wet firm brownish gray silty fine sandy clay w/trace of coarse sand.  6" RECOVERY  16" RECOVERY	A-6(4)	
9		4	8.0'	3 4 4 3	Saturated firm brownish gray silty fine sandy clay w/trace of coarse sand.	A-6(12)	
			10.0		22" RECOVERY		
12					*		
15							
18							

Remarks:

Reviewed By:	Soils Supervisor:

## **KEY TO SYMBOLS**

	_			
Symbol	Desc	זויו	) T. T. (	าท

## Strata symbols

Sand

Silty sand

Low plasticity clay

## Notes:

- 1. Exploratory borings were drilled on 5-10-2006 using a 3 1/4-inch diameter hollow stem auger.
- 2. No free water was encountered at the time of drilling or when re-checked the following day, unless recorded on 1st page.
- 3. Boring locations were taped from existing features and elevations extrapolated from survey unless otherwise reported.
- ). These logs are subject to the limitations, conclusions, and recommendations in this report.
- 5. Results of tests conducted on samples recovered are reported on the logs.