WELL COMPLETION REPORT MUST

	NCH INMENTAL CONTRO		MENTAL CONTROL  BE RETURNED 30 DAYS AFTER CONSTRUCTION DATE
ARE 19903		WELL COMPL	ETION REPORT
NO8.	3998	LOCAL ID 319	TYPE OF PERMANENT PUMP INSTALLED:
NER_ DO	Λ.		PUMP MANUFACTURE Cold
			RATED CAPACITY (GPM)
CONSTRUCTION DAT	E 2993	)	PUMP INTAKE SETTING 50 FT. BELOW GRADE
PURPOSE:   TES	т '	PERMANENT	THE COMPLETED WELL IS?
USE: DOMESTIC DAGRICULTURAL		☐ AGRICULTURAL	YES NO  A. AT LEAST 15' FROM ANY FOUNDATION
		□ INDUSTRIAL	D AT LEADT COLUMN AND ADDRESS OF THE COLUMN
☐ IRRIGATION		PUBLIC	C. AT LEAST 10' FROM TOWN SEWER LINE
☐ OBSERVATION		☐ DEWATERING	D. AT LEAST 100' FROM THE NEAREST EDGE
☐ HEAT PUMP RECHARGE ☐ HE		☐ HEAT PUMP SUPPLY	OF ANY TILE FIELD
☐ OTHER (Specify)			THE NEAREST NEIGHBORS (CIRCLE ONE)
IS THIS A REPLACEMENT WELL? YES D NO D			SEPTIC (LE FIELD CESSPOOL OR PRIVY
ABANDONMENT DATE FOR OLD WELL			IS 70 FROM COMPLETED WELL.
ABANDONMENT METHOD			IS COMPLETED WELL LOCATED AS SHOWN
			ON APPLICATION FORM?
DRILLING METHOD			IF NO, DESCRIBE LOCATION CHANGE OR OTHER COMMENTS.
☐ AUGERED	☐ BORED	☐ CABLE TOOL	" NO, DESCRIBE ESCAPION CHANGE ON OTHER COMMENTS.
D DRIVEN	□ JETTED	☐ AIR ROTARY	
MUD ROTARY	☐ REVERSE	□ WASHED	0:24-42
☐ OTHER (Specify)			DIA!
TOTAL DEPTH DRILLED 170			. 4
6	<b>CASING SEQUE</b>	NCE	The state of the s
	INNER	OUTER	
CASING TOP	14		
CASING BOTTOM	160		
CASING DIAMETER	24 41		
CASING MATERIAL	pu		
	SCREÉN SEQUI	ENCE	kamaran was a sa
	INNER	OUTER	MATERICAL
SCREEN TOP	160		
SCREEN BOTTOM	170		DRILLERS LOG DESCRIPTION TOP OF STRATA BOTTOM OF STRATA
SCREEN DIAMETER	29		
SCREEN MATERIAL	WOITTEN	ADDROVAL FOR CORFERENCE	· 10/154 0 3
	GRAVEL F	APPROVAL FOR SCREENING/ ACKING MORE THAN ONE AQU- T BE OBTAINED FROM DNREC.	Entrollo 3 9
GROUT TYPE: CEMENT □ BENTONITE CLAY □			Sy 9 19
FROM TO 160 FEET			Seed fly white 19 60
, , , , , , , , , , , , , , , , , , , ,			clares 60 85
NON GROUT BACKFILL OF WELL ANNULUS  TYPE FROM TO FEET			0 771-
GRAVEL PACK: TYPE # TO FEET			stand real of bt 85 124
			17972 4 124 sand m
STARIC WATER LEVEL: DATE \$\frac{2.9/20}{2.9/20}			500 134 136
FT_(Below, above) GROUND SURFACE			
PUMPING WATER LEVEL: FT. BELOW GRADE			2 ms fie 138 190
AFTER — 2— HOURS AT 30+ GPM.			San Dredge 120 180
WELL HEAD COMPLETION:			SUPPLEMENTAL DRILLERS LOG ATTACHED YES (), NO [2]

DOCUMENT NO. 40-08/78/01/03 - EC 7

OTHER \_\_\_\_

TYPE: PITLESS ADAPTOR

\_\_\_INCHES ABOVE GRADE.

PAGE 1 OF\_\_ PAGES

SIGNATURE OF DRILLER IN CHARGE:

COMPANY NAME \_\_\_