Ft.

Ft.

STATE OF DELAWARE **DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAYS**

Reference: Survey

Dia. U-Sample Boring: U-Samples:

F.A. Project: S.R. 26, Atlantic Avenue from Clarksville to Assawoman Canal	Boring No.:	IB # 50
Contract: 24-112-10		

Boring Location: Sta. 113+35, 150' Rt. C.L.

Boring Surface Elev.: +9.2'

Wt. of Casing Hammer: Wt. of Sample Hammer: Type of: D-Sampler: S-Sampler: U-Sampler: Average Fall:
Average Fall:
O.D. of Sampler:
O.D. of Samp. Tube:
O.D. of Samp. Tube:
O.D. of Rock Core: Lbs. Lbs. O.D. O.D. 30 Split-barrel Ŏ.D. Core Bit:

5.0

Casing Size: 5 217 Hollow Stem Auger: From Depth of: From Depth of: Inches 0.0 To: To: 3.5'

Water Level Readings Date Time Depth of Hole **Depth of Casing** Depth of Water

9.2 9.2 9.2 9.2 9.2 9.2

Ft.;

Ft.:

Pay Quantities: 2 1/2 in. Dia. Dry Sample Boring: No. of 2 in. Dia. Shelby Tubes: 2 1/2 in. Dia. Contin. Sample Boring:

Boring Contractor: Walton Corporation
Driller: Dave Burt

Helpers: Jason Truver & Wayne Hurd

Q;34-53

No. of:

Core Drilling in Rock:

Depth (ft.)	Daily Progress	No.	Sample Depth	Blows/6"	Sample Description	Class./G.I.	Remarks
3		1	2.0'	2 4 4 5	Moist loose brown fine sand w/some coarse sand and silt.	A-2-4(0)	
	·	2	3.5' 4.0' 5.0'	4 4 3 3	Wet loose brown silty fine sand w/some coarse sand. 22" RECOVERY 18" RECOVERY	A-2-4(0)	
6		3	5.0' 6.5'	2 2 3	Wet loose brown fine sand w/some coarse sand and silt. 16" RECOVERY	A-2-4(0)	
9					•		
12					-		
	:						
15							
18							

Remarks:

Reviewed By:	Soils Supervisor:	
•	 •	

KEY TO SYMBOLS

Symbol	Desci	rip	tion
--------	-------	-----	------

Strata symbols

Sand



Silty sand

Notes:

- Exploratory borings were drilled on 5-5-2006 using a 3 1/4-inch diameter hollow stem auger.
- 2. No free water was encountered at the time of drilling or when re-checked the following day, unless recorded on 1st page.
- 3. Boring locations were taped from existing features and elevations extrapolated from survey unless otherwise reported.
- 4. These logs are subject to the limitations, conclusions, and recommendations in this report.
- 5. Results of tests conducted on samples recovered are reported on the logs.