## STATE OF DELAWARE **DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAYS**

F.A. Project: S.R. 26, Atlantic Avenue from Clarksville to Assawoman Canal

Contract: 24-112-10 Boring Location: Sta. 161+25, 25' Lt. C.L.

**Boring Surface Elev.:** 

Reference:

Wt. of Casing Hammer: Wt. of Sample Hammer: Type of: D-Sampler: S-Sampler: U-Sampler: Core Blt: Average Fall: Average Fall: O.D. of Sampler: O.D. of Samp. Tube: O.D. of Samp. Tube: O.D. of Rock Core: Lbs. Lbs. O.D.

Casing Size: Hollow Stem Auger:

From Depth of: From Depth of:

To: To:

Water Level Readings Date 5/11/2006 Time 11:00 a.m.

Depth of Hole 7.0'

Depth of Casing

No. of:

Depth of Water 6.5'

Elev. of Water -6.5

7.0

Inches

Ft.; Ft.; Dia. U-Sample Boring: U-Samples:

Ft. Ft.

Boring No.: RB # 80

Pay Quantities: 2 1/2 in. Dia. Dry Sample Boring: No. of 2 in. Dia. Shelby Tubes: 2 1/2 in. Dia. Contin. Sample Boring:

Boring Contractor: Walton Corporation Driller: Dave Burt

Helpers: Jim Deal & Wayne Hurd

0:35-44

Core Drilling in Rock:

Depth (ft.)	Daily Progress	No.	Sample Depth	Blows/6"	Sample Description	Class./G.I.	Remarks
3		1			No Sample		
6		3			Moist brown coarse to fine sand w/some gravel and silt.  Wet brown coarse to fine sand w/trace of silt.	A-1-b A-1-b A-1-b	
9					Wet brown coarse to fine sand w/some silt.		
12		,					
15							
	]						

Remarks: Hand Auger

## **KEY TO SYMBOLS**

	_		
Symbol	Descr	lD	tion

Strata symbols

Sand

## Notes:

- 1. Exploratory borings were drilled on 5-11-2006 using a 3 1/4-inch diameter hollow stem auger.
- 2. No free water was encountered at the time of drilling or when re-checked the following day, unless recorded on 1st page.
- 3. Boring locations were taped from existing features and elevations extrapolated from survey unless otherwise reported.
- 1. These logs are subject to the limitations, conclusions, and recommendations in this report.
- 5. Results of tests conducted on samples recovered are reported