## MAIL TO:

WATER SUPPLY BRANCH DIVISION OF ENVIRONMENTAL CONTROL AND ENVIRONMENTAL CONTROL P.O. BOX 1401 DOVER, DELAWARE 19903

## STATE OF DELAWARE **DEPARTMENT OF NATURAL RESOURCES**

WELL COMPLETION REPORT MUS	S.
BE RETURNED 30 DAYS AFTER	_,
CONSTRUCTION DATE	l

PLEASE PRINT WELL COMPLETION REPORT					
PERMIT NO. 84707 LOCAL ID		TYPE OF PERMANENT PUMP INSTALLED:			
OWNER SYLVES	TER BRIDDEL	.L.	PUMP MANUFACTURE A	ERMOTOR	
CONSTRUCTION DAT	<sub>E</sub> 11/02/90		T HATED CAPACITY (GPM)	.0	
CONSTRUCTION DATE 11/02/90 PURPOSE:   TEST PERMANENT		PUMP INTAKE SETTING 30 FT. BELOW GRADE THE COMPLETED WELL IS?			
USE: TOOMESTIC		- ACDICITION			YĘŞ NO
E10014/150014		☐ AGRICULTURAL	A. AT LEAST 15' FROM ANY FOUNDATION		
III JARIGATION		☐ INDUSTRIAL	B. AT LEAST 50' FROM ANY SEPTIC TANK		
☐ OBSERVATION		□ PUBLIC	C. AT LEAST 10' FROM TOWN SEWER LINE		
			D. AT LEAST 100' FROM TH	E NEAREST EDGE	
☐ HEAT PUMP RECHARGE ☐ HEAT PUMP SUPPLY ☐ OTHER (Specify)			OF ANY TILE FIELD		
IS THIS A REPLACEM			THE NEAREST N	ieighbors (C	IRCLE ONE)
APANDONIACHT DAT	E FOR OLD WITH	NOW	SEPTIO TILE FIELD CESSPOOL OR PRIVY		
ABANDONMENT DATE FOR OLD WELL  ABANDONMENT METHOD			IS _58' FROM COMPLETED WELL.		
THE WILLIAM WILL	HOD	/ PST	IS COMPLETED WELL LOCATED AS SHOWN		
MUD ROTORY			ON APPLICATION FORM?		
□ AUGEDED	DRILLING MET		IF NO, DESCRIBE LOCATION	N CHANGE OR OTH	IER COMMENTS.
□ AUGERED	□ BORED	CABLE TOOL	1		1
DRIVEN	□ JETTED		]		/ /
MUD ROTARY	м <del>Ū</del> D <sup>R</sup> ĘХ <del>БЛСБ</del> RY	□ WASHED	1 カルルフ・	·	1 1
OTHER (Specify)	95		K157~01		л 00 д
TOTAL DEPTH DRILLE	D		1 11201		
	040010 07011		K134-01 AH:40	ותו	(
	CASING SEQUE	NCE	1 11.40	UUI NOV 2 (	170gg
******	1 'ABOVE	OUTER	1 Alt. 1		( '''''
CASING TOP	95	<del></del>	1 '		
CASING BOTTOM	4		1	WATER S	SUPPLY
CASING DIAMETER	PVC		į <b>-</b>	A SA CI E I I	DUT TIY
CASING MATERIAL					
	SCREEN SEQUE				
000000	INNER	OUTER	į		
SCREEN TOP	90				
SCREEN BOTTOM	95		DRILLERS LOG DESCRIPTION	TOP OF STRATA	BOTTOM OF STRATA
SCREEN DIAMETER	4		FINE TAN SAND	1	
SCREEN MATERIAL	PVC   WRITTEN	APPROVAL FOR SCREENING	CLAY	+ 0	20
/	GRAVEL P	APPROVAL FOR SCREENING/ ACKING MORE THAN ONE AQU- I BE OBTAINED FROM DNREC.	GRAY SAND CLAY	20	30
CDOUT TUBE OF LE			GRAY CLAY	3.0	50
GROUT TYPE: CEME		CLAY 🗆	MEDIUM GRAY SANI	<del>5 50</del>	60
OTHER: _0T			COURSE GRAY SAN	<u> </u>	95
				,	
NON-GROTTE ACKEIL	L OF ANDELL ANNULU	<b>9</b> 5			
TYPE FREE FREE FREE FREE FREE FREE FREE FR	10M# <del>3 WASITE</del>	FEET			
FROM 85	0 95				
FROM 00 TO 95 FEET STATIC WATER LEVEL: DATE 11/02/90					
24 FT. (Below, 165%) GROUND SURFACE					
PUMPING WATER LEVEL:30 FT. BELOW GRADE					
AFTER 2 HOURS AT 35.00 GPM.				<del> </del>	
nouns AI 30.00 GPM.				<u> </u>	
WELL HEAD COMPLETION:					
			SUPPLEMENTAL DRILLERS L	OG ATTACHED Y	ES □ NO DX
TYPE: PITLESS ADAPTOR XI OTHER CI			PAGE 1 OF1 PAGES		1
8 INCHES ABOVE GRADE.			COMPANY NAME BURNS WELL DRILLING		
			SIGNATURE OF DRILLER IN CHARGE: DATE 11/14/00		
			Ernest Smith		
· · · · · · · · · · · · · · · · · · ·			- Junior		