


DC 53-99

	MWH Americas, Inc. 335 Phoenixville Pike Malvern, Pennsylvania 19355	Boring ID: 1M Page 1 of 3	DC53-99
	Project Name: from URS gINT database urs_excel_3_19_06.gpj Location: Delaware City, DE Project Number: Date Started: 9/16/2002 Date Finished: 9/16/2002 Drilling Method: Hollow Stem Auger Sampling Method: State Permit Number: NA	Boring Location: Delaware City Refinery Drilling Company: Walton Corporation (Gary Truver Sr.) Ground Elevation (ft/msl): 26.2 Total Depth (ft): 65.5' Boring Diameter (in): " Water Level During Drilling (ft/bgs): Not Measured Weather Conditions: Logged By: Vince Piazza	

Depth (feet)	Blow Counts	Recovery (inches)	PID (ppm)	Sample ID	Sample Interval	USCS	Lithology	Lithologic Description	Well Diagram	Remarks
0								0' - 0.8' FILL - angular stone		
						SP		0.8' - 2.5' brown SAND, SILT and GRAVEL		
						SP		2.5' - 3.5' brown SAND + trace SILT and GRAVEL		
						SP-SM		3.5' - 6.5' Gray, fine SAND + trace SILT		
5						SP-SM		6.5' - 9.5' gray-brown, fine SAND + trace SILT		
10						SM		9.5' - 16.5' brown, silty, fine SAND		
15						SM		16.5' - 65' brown, silty fine SAND + trace CLAY		
20										
25										
30										



Depth (feet)	Blow Counts	Recovery (inches)	PID (ppm)	Sample ID	Sample Interval	USCS	Lithology	Lithologic Description	Well Diagram	Remarks
30										
35										
40										
45										
50										
55										
60										
65						CL		65' - 65.5' dark gray CLAY and little		

65 km.
 not indicative

DC53-97



MWH

MWH Americas, Inc.
335 Phoenixville Pike
Malvern, Pennsylvania 19355

Boring ID: 1M

Page 3 of 3

Depth (feet)	Blow Counts	Recovery (inches)	PID (ppm)	Sample ID	Sample Interval	USCS	Lithology	Lithologic Description	Well Diagram	Remarks
70								mica + trace very fine SAND		
75										
80										
85										
90										
95										
100										