

Dc54-25

26
Dc54-27A

DEPTH IN FEET SAMPLES
BORING 1-2
SURFACE ELEVATION +24.7

DEPTH IN FEET SAMPLES
BORING 1-3
SURFACE ELEVATION +24.6

BLOW COUNT	SYMBOLS	DESCRIPTIONS
0		DARK BROWN SLIGHTLY MICACEOUS SILTY CLAY WITH LIMONITE STAINING (MEDIUM STIFF)
5	CH	GRADING SOFT
10	OH	DARK GRAY SLIGHTLY MICACEOUS ORGANIC SILTY CLAY (SOFT)
15	CL	MOTTLED GRAY AND ORANGE BROWN SLIGHTLY MICACEOUS SILTY CLAY, TRACE FINE SAND (SOFT)
20	SC	YELLOWISH BROWN MEDIUM TO FINE SAND, LITTLE TO SOME SILTY CLAY (LOOSE) GRADING FINER
25	SC	GRADING VERY LOOSE GRADING TO GRAYISH BROWN SILTY CLAY, SOME COARSE TO FINE SAND, WITH OCCASIONAL GRAVEL-SIZED PIECES OF REDDISH BROWN CEMENTED SAND (SOFT)
30	OH	GRADING BROWNISH GRAY, AND FINE SAND DARK GRAY SLIGHTLY MICACEOUS ORGANIC SILTY CLAY, SOME PEAT (MEDIUM STIFF) GRADING WITH SOME GRAY FINE SAND IN LAYERS
35	PT OH	BLACK TO DARK BROWN PEAT AND ORGANIC SILTY CLAY (MEDIUM STIFF TO STIFF)
40	SC CL	LAYERED SLIGHTLY REDDISH GRAY AND LIGHT GRAY SLIGHTLY MICACEOUS FINE SAND, SOME SILTY CLAY (MEDIUM DENSE) GRADING SLIGHTLY FINER, WITH TRACE ORGANIC MATTER

BLOW COUNT	SYMBOLS	DESCRIPTIONS
0		BROWN SLIGHTLY MICACEOUS SILTY CLAY (SOFT TO MEDIUM STIFF)
5	CH	GRADING GRAY IN COLOR, SLIGHTLY ORGANIC, WITH LIMONITE STAINING
10	OH	DARK GRAY SLIGHTLY MICACEOUS ORGANIC SILTY CLAY (SOFT) LAYERS OF ROOTS
15	OH	
20		GRADING GRAY IN COLOR AND MEDIUM STIFF
25	PT OH	BLACK TO DARK BROWN PEAT AND ORGANIC SILTY CLAY (SOFT)
30		BROWNISH GRAY SILTY CLAY (TOP 2" MIXED WITH PEAT) (SOFT) GRADING MICACEOUS GRADING GRAYISH BROWN
35	CH	GRADING VERY MICACEOUS AND WITH LIMONITE STAINING GRADING MEDIUM STIFF
40		GRADING BROWNISH GRAY GRADING WITH YELLOWISH BROWN MOTTLING GRADING DARK GRAY WITH ORANGE MOTTLING
45		GRADING WITH TRACE SHELL FRAGMENTS
50	CL	GRADING WITH TRACE ROOT FIBERS DARK GRAY SLIGHTLY MICACEOUS SILTY CLAY, SOME SLIGHTLY GREENISH GRAY GLAUCONITIC FINE SAND (STIFF)
55		GRADING VERY STIFF

BORING COMPLETED AT A DEPTH OF 42 FEET ON 11/25/75
15 FEET OF 4 INCH DIAMETER CASING USED
GROUNDWATER AT A DEPTH OF 12 FEET ON 11/26/75 (BOREHOLE HAD CAVED IN AT A DEPTH OF 13 FEET AT THIS TIME)

BORING COMPLETED AT A DEPTH OF 55 FEET ON 12/2/75
35 FEET OF 4 INCH DIAMETER CASING USED
GROUNDWATER AT A DEPTH OF 9.1 FEET ON 11/25/75 WITH NO CASING IN GROUND

LOG OF BORINGS