D	ATE:	·Augus	t 6, 199	LOG of BORING NO. B-2 SURFACE ELEVATION: 29.2	LOCAT	ION: _	See	She Figur	et 1	of 2
о оертн. п	SAMPLES	N VALUE OR CORE RECOVERY	SAMPLE TYPE	DESCRIPTION	STRATUM	POCKET PENETROMETER	WATER CONTENT, %	LIQUID LIMIT, %	PLASTIC LIMIT. %	OTHER TESTS
0 .	-	12 13	SS SS	Very stiff gray and brown sandy silt with roots, and with silty sand layer from 3.0 to 3.3 feet	25.2	<u>tsf</u> 4.5+ 2.0				
5 -		4	SS	Stiff. becoming very soft, dark gray micaceous organic silt with organic inclusions	25.2	1.0			i	
		8	SS	·		0.5 0.5- 0.3				
10 -		6	ST			0.5				
15 -		. 2	SS			0.3	73.9			
20 -	-	1	SS	with 2-inch-thick layers of silty fine sand		0.2	54.3			
0.5		woh	ST			0.3				
25 -		15	SS	Stiff orange-brown and light gray mottled sandy clay, becoming clayey sand Medium dense orange-brown silty sand with	0.2	1.75				
	-	13	SS	sandy clay seams with occasional cemented sand seams						
35 -				Continued on Sheet 2 of 2						
Pro Pro	oject I oject I	No.:9 Name:	98G105 Star E	Interprise DMSA III	n: <u>10.0</u>	ft / ft /	After After After		hi hi	rs rs
Drilling Method: Hollow-Stem Augers and Mud Rotaryft Afterhrs										

GeoSystems Consultants

LOG of BORING NO. B-2 DATE: August 6, 1998 SURFACE ELEVATION: 29.2 LOCATION: See Figure 1								of 2		
DATE		: August 6, 1998		SURFACE ELEVATION: 29.2	LUCAI	366				
DEPTH, ft	SAMPLES	N VALUE OR CORE RECOVERY	SAMPLE TYPE	DESCRIPTION	STRATUM	POCKET PENETROMETER	WATER CONTENT, %	LIQUID LIMIT, %	PLASTIC LIMIT, %	OTHER TESTS
35				Same as above	-7.8	<u>tsf</u>				
40 -	-	24	SS	Medium dense gray micaceous fine sand, trace silt			·			
45 -	-	18	SS	,						
50 -	-	16	SS	becoming dark gray micaceous silty fine sand	-20.8	į				
55 -						-				
60 -										
65 -										-
	\perp				. 45.5		\ 6 4	4-9		
	Completion Depth: 50.0 ft Water Depth Wate				1: <u>10.0</u>		After After		hr hr	
Project No.: 98G105 ft After Project Name: Star Enterprise, DMSA III ft After										
Drilling Method: Hollow-Stem Augers and Mud Rotary ft After hrs										s