

DESCRIPTIVE LOG

Sha

DGS No. PC 41-5

Drilling Method PC-5 Auger

Date Drilled 8/12/68

Local No. PC 41-5

Project Nantuxke

Logged by Jordan & Talley

Ditch Samples

Cores

<u>Depth</u>	<u>Lithology</u>	<u>Depth</u>	<u>Lithology</u>
0 - 3.5'	Clay, yellow and sand, brown with some gravel. Sampled 1 bag.	2.5-3.5	Corkscrew augers - Sampled 1 bag.
3.5-4	Sand, clayey, red Sampled 1 bag	3.5-4'	Corkscrew. Sampled 1 bag
4-5	Silt, clayey, sandy, mottled gray, red, and brown Sampled 1 bag.	4-5	Corkscrew - Sampled 1 bag
(Wicker tangle at 3' pool returns below)			
5-9	above - grading to sand.		
9-10.5	Clay, gray, mottled with green. Very fine and clay. Small pieces of clayey sand on bottom	9-10.5	Split spoon core. 4" recovery. Clay, gray, mottled with green; very fine and clay. Small pieces of clayey sand on bottom half up to about 6 1/2" thick. One specimen seen in second core. Possible borings

DESCRIPTIVE LOG

DGS No. PC41-5 Drilling Method _____ Date Drilled _____
 Local No. _____ Project _____ Logged by _____

Ditch Samples

Cores

<u>Depth</u>	<u>Lithology</u>	<u>Depth</u>	<u>Lithology</u>
10.5-19 (approx)	Sand, clayey, grading to clay, dark gray with fresh wood. 2 bags of sample.		
19-33.5	Clay, gray becoming sandier. Wood fragments. Some sand lenses.		
33.5-34 TD	Sand, coarse and gravel.		