MAIL TO:

STATE OF DELAWARE DEPARTMENT OF NATURAL RESOURCES BE RETURNED 30 DAYS AFTER

WELL COMPLETION REPORT MUST

WATER SUPPLY BRANCH

DIVISION OF ENVIRONMENTAL CONTROL AND ENVIRONMENTAL CONTROL GONSTRUCTION DATE						
P.O. BOX 1401 DOVER, DELAWARE 19903						
	903 Pg77-03 WELL COMPL	ETION REPORT	ĭ			
PLEASE PRINT				_		
PERMIT NO 855	-3.9 LOCAL ID	TYPE OF PERMANENT PUMP INSTALLED:				
J. H. W.	LITERSON YSON FILE					
OWNER BLUE HERON ESTATE: WATER CO.		PUMP MANUFACTURE				
		RATED CAPACITY (GPM)				
	OCT 35, 1991	PUMP INTAKE SETTING FT. BELOW GRADE				
PURPOSE: TEST	PERMANENT	THE COMPLETED WELL IS?				
				YES NO		
USE: DOMESTIC	☐ AGRICULTURAL	A. AT LEAST 15' FROM ANY FOUNDATION				
□ COMMERCIAL		B. AT LEAST 50 FROM ANY SEPTIC TANK G. AT LEAST 40 FROM A SOUND SEMESTING TO THE SERVICE OF T				
☐ IRRIGATION	CL_PUBLIC	C. AT LEAST 10' FROM TOWN SEWER LINE				
□ OBSERVATIO	N □ DEWATERING RECHARGE □ HEAT PUMP SUPPLY	D. AT LEAST 100° F ROM THE NEAREST EDGE — OF ANY TILE FIELD				
☐ OTHER (Spec		THE NEAREST NEIGHBORS (CIRCLE ONE)				
	NT WELL? YES [] NO [2]	SEPTIC TILE FIELD CESSPOOL OR PRIVY IS 180 FROM COMPLETED WELL.				
	FOR OLD WELL A//A					
ABANDONMENT METHO	• .	IS COMPLETED WELL LOCATED AS SHOWN				
	•	ON APPLICATION FORM?	, +			
	DRILLING METHOD	IF NO, DESCRIBE LOCATION CHANGE OR OTHER COMMENTS.				
☐ AUGERED	☐ BORED ☐ CABLE TOOL					
☐ DRIVEN	☐ JETTED ☐ AIR ROTARY	1				
729-MUD ROTARY	□ REVERSE □ WASHED	· ·				
OTHER (Specify)						
TOTAL DEPTH DRILLED	70'					
	212112 25215125		-			
(CASING SEQUENCE					
0.40 0.70	INNER OUTER		-100 (-100 (14 15 - 15 - 15 - 15 - 15 - 15 - 15 - 15 -		
CASING TOP	60'	ł		397		
CASING BOTTOM CASING DIAMETER	4/a"					
CASING DIAMETER	P.V.C.					
-	SCREEN SEQUENCE					
	INNER OUTER					
SCREEN TOP	60'					
SCREEN BOTTOM	70'	DRILLERS LOG DESCRIPTION	TOP OF STRATA	BOTTOM OF STRATA		
SCREEN DIAMETER	4/3"	TOP SUIL	0.	, ,		
SCREEN MATERIAL	P.V.C.	101 3012				
	WRITTEN APPROVAL FOR SCREENING/ GRAVEL PACKING MORE THAN ONE AQU- IFER MUST BE OBTAINED FROM DNREC.	DIRTY TANSAND+CLA	4 / '	/.3 ′		
		FINE WHITE SAND	/ /= /	24'		
GROUT TYPE: CEMENT □ BENTONITE CLAY 2		_	- / - / - 	,		
OTHER:TO		FINE-COARSE TAN SAN	<u> 24</u>	36		
NON-GROUT BACKFILL		FINE-CUARSE ORANGES	1NO 36	55		
TYPE FROM THE TYPE		F.N.F. MEA COM		61'		
GRAVEL PACK: TYPE		TIME MEDIUM MELLOWS		Ψí		
FROM	ン <u> ・ デ ・ FEET</u>	VERY FIRE TO				
•	DATE 067 25 21	COARSE ARANCE				

WELL HEAD COMPLETION:

PUMPING WATER LEVEL: 12 FT. BELOW GRADE AFTER 3 HOURS AT 65 GPM.

TVDE	DITI COS	ADAD	TOR L
I T P E :	PULESS	ADAP	IUN LS

OTHER

—

12_INCHES ABOVE GRADE.

SAND

DATE

Mer. 26, 1991

SUPPLEMENTAL DRILLERS LOG ATTACHED YES
NO E-

PAGE 1 OF __ PAGES COMPANY NAME White Dulling

SIGNATURE OF DRILLER IN CHARGE: