Pg 55-09

WALTON CORPORATION
Drilling Contractor
P. O. BOX 1097, NEWARK, DELAWARE 19711

BORING LOG

NAME Townsend Inc. PROJECT NO. 130
Millsboro, DE. SUPERVISOR ---

BORING NO.	DRILLER	DATE
MW - 1	G. Truver	10-27-77
WEATHER	**SURFACE ELEVATION**	**DATUM**
Foggy & Warm	22.2 ft.	U.S.G.S. (approx.)

Sample No.	Sample Depth - Feet From	Sample Depth - Feet To	Depth Strata Feet From	Depth Strata Feet To	Driller's Description of Materials	*Blows A		
			0	1.0	Top Soil			
1	1.0	2.0	1.0	3.0	Brn. F Sand w/Tr. Silt 2	2	2	3
2	4.0	6.0	3.0	5.5	Brn. Silt w/Tr. F Sand 3	4	5	6
			5.5	6.0	Brn. F/M Sand w/Tr. Silt			
3	6.0	8.0	6.0	8.5	Brn. F Sand w/Tr. Silt 7	11	10	8
					w/2" Silty F/M Sand Layer			
4	9.0	11.0	8.5	12.5	Brn. & Gray F Sand w/Tr. Silt 2	3	3	4
5	14.0	16.0	12.5	18.0	Brn. & Gray F/M Sand w/Tr. Silt 2	3	4	7
6	19.0	21.0	18.0		Brn. & Gray F/M Sand w/Tr. Silt 3	5	5	7
7	24.0	26.0		26.0	Brn. & Gray F/M Sand w/Tr. Silt 4	3	5	7

*A Number of blows of 140 lb. hammer dropped 30 in. required to drive 2 in. split-spoon sampler for each of three 6 in. increments.

* B Number of blows of 300 lb. hammer dropped 18 in. required to drive ..... in. casing 12 inches.

REMARKS: Sample Wet @ 20.5
Screen interval: 15.8 to 26.6 ft.

GROUND WATER

21.4 ft.	10/27/77

BLOWS ON CASING B

0- 1
1- 2
2- 3
3- 4
4- 5
5- 6
6- 7
7- 8
8- 9
9-10
10-11
11-12
12-13
13-14
14-15
15-16
16-17
17-18
18-19
19-20
20-21
21-22
22-23
23-24
24-25
25-26
26-27
27-28
28-29
29-30
30-31
31-32
32-33
33-34
34-35
35-36
36-37
37-38
38-39
39-40
40-41
41-42
42-43
43-44
44-45
45-46
46-47
47-48
48-49
49-50
50-51
51-52
52-53
53-54
54-55
55-56
56-57
57-58
58-59
59-60
60-61