

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY  
WATER RESOURCES DIVISION

PH 51-9

WELL SCHEDULE

Date: February 10, 1956 Field No. 2-0  
Record by: Jack Coskey Office No. PH 51-9  
Source of data: Mr. Mullins, Log Correr, & Test Boring Data

1. Location: State Delaware County Sussex

Map:  $\frac{1}{2}$  sec.  $\frac{1}{4}$  sec. T N S R E W

2. Owner: Del. Power & Light Co. Address Salisbury, Md.

Driller: Winters Eng. & Constructors Inc. Address Philadelphia, Pa.

3. Topography: C.P. (Island)

4. Elevation: 8 ft. above MSL

5. Type: Dug, drilled, driven, bored, jetted, 1955

6. Depth: Rept. 90 ft. Meas. ft.

7. Casing: Diam. in., to in., Type ft., Finish

8. Chief Aquifer: ft. to ft.

9. Water level: 8.0 ft. Rept. 1955 above below

10. Pump: Type N Capacity G. M. which is ft. above ft. below surface

Power: Kind Horsepower

11. Yield: Flow G. M., Pump G. M., Meas., Rept. Est.

Drawdown ft. after hours pumping G. M.


12. Use: Dom., Stock, PS, RR., Ind., Irr., Obs. TEST BORING

13. Quality: Adequacy, permanence Temp Yes Taste, odor, color Sample No.

Unit for Log

14. Remarks: (Log, Analyses, etc.) 709

SEE BACK of PH 51-9 for Location



- PH51-9
- 0 - 2 Loam (topsoil?) and sand, medium, brown
- 2 - 9 Sand, medium to coarse, brown
- 9 - 18 Sand, coarse, brown and white, with traces of gravel
- 18 - 32 Sand, coarse, brown and white, with traces of gravel
- 32 - 52 Sand, Coarse, gray, with traces of gravel
- 52 - 75 Sand, coarse, brown, and gravel
- 75 - 80 Sand, coarse, gray and gravel
- 80 - 83 Sand, fine, gray, silty
- 83 - 90 Sand, fine, gray

PH 51-9