- 1	· · · · · ·		71-8-25	The state of the s	
CUSTOMER Delmarva Power a			nd Lig	ht	Joe 5631
ADDRESS Indian River Pow			er Plant, Millsboro, Delaware		of the state of th
L OCATIO	N 200	yards W of	Main G	ate and 60' South of roa	d
		FEET FROM GROUND SURFACE O TO		WELL LOG	
GROUND		0–5		Fine sand and sas coal	
1		5–88		Medium to coarse tan sand	
↑		88-90		Gray clay	
		90–115		Fine gray sand	
		115–119		Gray clay	
	2	119-135		Fine to medium gray sand	
257		135-137		Gray clay and wood	
		137-148		Fine gray sand w/streaks of clay	
		148-174		Gray clay and wood, and fine sand	
JEP T		174-232		1 Fine to medium gray sand	
TOTAL DEPTH		232-235		Gray clay	
		235-265		Fine to medium gray sand	
		265-280		Fine to medium gray sand and clay	
		280-300		Clay and fine sand	
	SCREEN (X)				
WELL NO DIAMET			DIAMETE	R OF WELL 4"	DEPT, OF WELL256!
HRS. PUMPED 3 SLOT				ZE016	TYPE OF CASING PVC
CAPACITY G.P.M. 60 DRI			DRILLIN	G MACHINE NO	LENGTH OF CASING236 *
STATIC LEVEL 2'5" DRIL			DRILLER	Cowgill & Kelley	DISTANCE TO TOP OF SCREEN 236-256
PUMPING LEVEL 14'4" GRAVE			GRAVEL .	# 2 & 3	TYPE SCREEN PVC
			BAGS OF	CEMENTO	SIZE OF SCREEN 4"
PUMPED WITH air & pumper DATE				LL COMPLETED 9-3-80	1
	CEMENT GROUT		DRILLER	's HELPERWallace & Myer	Cowgill & Kellev
DEPTH GRAVEL PACKED200-2561					WELL DRILLER'S SIGNATURE

...