STATE OF DELAWARE

DEPARTMENT OF NATURAL RESOURCES

WELL COMPLETION REPORT MUST
BE RETURNED 30 DAYS AFTER
CONSTRUCTION DATE

. ∕.O. BOX 1401	ONMENTAL CONTROL	AND ENVIRONM	MENTAL CONTROL	CONSTRUCTION	DATE
DOVER, DELAWARE 19903 PLEASE PRINT WELL COM			ETION REPORT		
PERMIT NO. 89528 LOCAL		OCAL ID	TYPE OF PERMA	NENT DUMP	INISTALLED.
OWNER_Tunnell Companies, L.P.			PUMP MANUFACTURE	Na,	INSTALLED;
P.O. Box 368, Millsboro, DE 19966			RATED CAPACITY (GPM)		
CONSTRUCTION DATE 03/31/92			PUMP INTAKE SETTING FT. BELOW GRADE		
PURPOSE: TEST X PERM		PERMANENT	THE COMPLETED WELL IS?		
USE: DOMESTIC DAGRICULTURAL			ł		YES NO
□ COMMERC	-	AGRICULTURAL INDUSTRIAL	A. AT LEAST 15' FROM ANY FO	UNDATION	છ ⊢ □
□IRRIGATION		PUBLIC	B. AT LEAST 50' FROM ANY SEPTIC TANK		
☐ OBSERVAT		DEWATERING	C. AT LEAST 10' FROM TOWN	SEWER LINE	⊠ □
		HEAT PUMP SUPPLY	D. AT LEAST 100' FROM THE NEAREST EDGE (25) OF ANY TILE FIELD		
OTHER (Specify)			1	COUPAR (A	******
IS THIS A REPLACEMENT WELL? YES INO IN			THE NEAREST NE	SSPOOL OR F	IRCLE ONE)
ABANDONMENT DATE FOR OLD WELL			IS 100+ FROM COMPLETE	D MEII	HIVY
ABANDONMENT METHOD			IS COMPLETED WELL LOCATED AS SHOWN		
		_	ON APPLICATION FORM?	-0 ,	1254- □
DRILLING METHOD DI AUGERED DI CARLETTONI			IF NO, DESCRIBE LOCATION (HANGE OR OTH	
D DRIVEN	□ BORED	CABLE TOOL			l
MUD ROTARY	□ JETTED □ REVERSE	☐ AIR ROTARY	72.5	ים	1
OTHER (Specify)	□ HEVEHOE	□ WASHED	Ro 2	<u> </u>	1
TOTAL DEPTH DRILLED			1 ~	A	
			1 (1)131-12	7	- 10
	CASING SEQUENC	·c		1	Mis wess!
	INNER	OUTER]	1	5 /4
CASING TOP	12'	AA (EU	* This MAS 1200'E		Me wee
CASING BOTTOM	8.4			yw	7 /4
CASING DIAMETER	8"		IN EGS	:	2/0
CASING MATERIAL PVC				· .	* 3
SCREEN SEQUENCE				(D-L	9 N
	INNER.	OUTER]		
SCREEN TOP	110		MB		•
SCREEN BOTTOM			DRILLERS LOG DESCRIPTION I	OP OF STRATA	BOTTOM OF STRATA
SCREEN DIAMETER SCREEN MATERIAL	5.5.		Top soil	0	i
GOUPER MYTERIAL		OVAL FOR SCREENING/			1
CDOLIT TYPE OF US		OVAL FOR SCREENING/ NG MORE THAN ONE AQU- OBTAINED FROM DNREC.	Brown clay Tan fine to med sand		5
GROUT TYPE: CEMENT □ BENTONITE CLAY 🔼 OTHER:				5	19
FROM			White clay	19	30
NON-GROUT BACKFILL OF WELL ANNULUS			Ian fine to coarse sand w/gravel		
TYPE FROM TO FEET			Tan hine to coarse		
GRAVEL PACK: TYPE # 2			sand w/gravel	80	115
FROM 65 TO 1/5 FEET 7			Gray clay	115	118
STATIC WATER LEVEL	.: DATE <u>-シ/ラ// 7</u> シノ	<u>, </u>	Tan fine to coarse		
FT. (Below, abo	FT. (Below, above) GROUND SURFACE			118	121
PUMPING WATER LEVEL: 4 FT. BELOW GRADE					
AFTER HOURS AT GPM.					
WELL HEAD COMPLETION:			CUIDDI FAIRATAN DONA	···	
TYPE: PITLESS ADAPTOR [7]			SUPPLEMENTAL DRILLERS LOG ATTACHED YES D NOXX		
OTHER & CAPACO			PAGE 1 OF _ / PAGES COMPANY NAMEAMERICAN Water Well Systems, Inc.		
24_INCHES ABOVE GRADE.			SIGNATURE OF DRILLED IN CHARGE		

A SUPPLY BRANCH