

VE - fine sand = 8' - 18' BGS
 med SAND = 18' - 25' BGS
 Q6L3-10



DUFFIELD ASSOCIATES

Consultants in the Geosciences

OBSERVATION WELL OB-4

Permit No : 212421

(Page 1 of 2)

The Landings at Pepper Creek
 Hydrogeological Evaluation
 Dagsboro, DE
 6143.YC

Date Started : November 30, 2005
 Date Completed : November 30, 2005
 Logged by : JSD
 Weather : Sunny, 60's
 Driller/Agency : G Truver Sr./Walton Corp

Drilling Equipment : ATV-mounted CME 55
 Drilling Methods : 4.25" H.S.A.
 Surface Elevation : 17.0 feet
 Northing : 63,641 U.S. Meters DE SPC NAD 83
 Easting : 218,233 U.S. Meters DE SPC NAD 83

Depth in feet	Surf. Elev. 17.0 ft	GRAPHIC	USCS	USDA	Sample Condition	Water Levels	SAMPLES	Sample Number	Blows per 6 inches	Recovery (ft)	Well Construction Details	WATER LEVEL	Observation Well 212421 Top of Well Elev. PVC = 19.75 Steel Casing Rim 19.81 Surf. Elev. 17.0 ft
					Remolded	During Drilling							
0	16.7							1A	1-1-3-3	1.8			
								1B					
2			SP	S				2	2-2-2-3	1.4	2" Schedule 40 PVC Solid Well Casing		
4								3	2-2-3-2	1.7			
6	10.8		SP-SM	LS/S				4A	3-4-4-4	1.5	Cement/Bentonite Grout		
10.3			SP	S				4B					
								4C					
8	9.0							5	2-4-5-6	1.7			
10			SM	LS/SL				6	7-7-7-7	2.0			
12								7	3-4-6-5	1.8			
14											Sand Pack - #2 well sand		4.5

- NOTES:
1. Test boring terminated at 25.0 feet +/- below existing ground surface (b.e.g.s.).
 2. Some topsoil removed for previous clearing.
 3. Wet-on-spoon at 14.0 feet +/-; water level within the augers at 13.4 feet +/- with the bottom of the augers at 14.0 feet +/- b.e.g.s.
 4. Observation Well MW-1 (DNREC ID 212421) installed upon completion.
 5. Auger boring performed in general accordance with ASTM D 1452.
 6. Split-barrel sampling performed in general accordance with the Method for Penetrative Test and Split-Barrel Sampling (ASTM D 1586).
 7. Soil descriptions performed in general accordance with ASTM D 2488, the Practice for Description and Identification of Soils (Visual-Manual Procedure).



DUFFIELD ASSOCIATES

Consultants in the Geosciences

OBSERVATION WELL OB-4

Permit No : 212421

(Page 2 of 2)

The Landings at Pepper Creek
Hydrogeological Evaluation
Dagsboro, DE
6143.YC

Date Started : November 30, 2005
Date Completed : November 30, 2005
Logged by : JSD
Weather : Sunny, 60's
Driller/Agency : G Truver Sr./Walton Corp

Drilling Equipment : ATV-mounted CME 55
Drilling Methods : 4.25" H.S.A.
Surface Elevation : 17.0 feet
Northing : 63,641 U.S. Meters DE SPC NAD 83
Easting : 218,233 U.S. Meters DE SPC NAD 83

Depth in feet	Surf. Elev. 17.0 ft	GRAPHIC	USCS	USDA	Sample Condition	Water Levels	SAMPLES	Sample Number	Blows per 6 inches	Recovery (ft)	Well Construction Details	WATER LEVEL	Observation Well 212421
					<input checked="" type="checkbox"/> Remolded	<input type="checkbox"/> During Drilling							
DESCRIPTION													
14													
16			SM	LS/SL				8	2-3-3-3	1.9			2.2
18	-1.0												
20	-3.0		SP-SM	LS/S				10	WR-WR-4-6	1.1	2" Schedule 40 PVC Screened Well Casing - 0,020 slot		
22	-5.0		SC-SM	LS				11	4-6-4-7	2.0			
24	-6.5		SP-SM	LS/S				12	2-2-6	1.0			
26	-8.0		SP-SM	LS/S				13	7-9-11	0.9			-7.3 -7.9

NOTES:

1. Test boring terminated at 25.0 feet +/- below existing ground surface (b.e.g.s.).
2. Some topsoil removed for previous clearing.
3. Wet-on-spoon at 14.0 feet +/-; water level within the augers at 13.4 feet +/- with the bottom of the augers at 14.0 feet +/- b.e.g.s.
4. Observation Well MW-1 (DNREC ID 212421) installed upon completion.
5. Auger boring performed in general accordance with ASTM D 1452.
6. Split-barrel sampling performed in general accordance with the Method for Penetrative Test and Split-Barrel Sampling (ASTM D 1586).
7. Soil descriptions performed in general accordance with ASTM D 2488, the Practice for Description and Identification of Soils (Visual-Manual Procedure).