



Qh23-03 ✓

CUSTOMER JOHN PLUMMER - THE POINT FARM (PAGE 1) JOB H0531
 ADDRESS SALISBURY MD 21801 DATE 8-11-87
 LOCATION 100'NW of Creekside Drive and 250'S of Viners Lane

GROUND	2'	FEET FROM GROUND SURFACE	WELL LOG
		0 TO.....	
↑ 283' TOTAL DEPTH ↓	263'	0 - 1	top soil
		1 - 4	tan fine sand
		4 - 5	clay
		5 - 12	tan fine to med sand
		12 - 17	white fine to med sand w/ white clay
		17 - 31	tan fine to coarse sand
		31 - 43	white fine to med. sand
		43 - 83	tan fine to coarse sand w/ gravel
		83 - 84	iron ore
		84 - 103	tan fine to coarse sand w/ gravel
		103 - 118	white fine to coarse sand iron ore
		118 - 125	gray clay
		125 - 140	gray fine to med sand w/ clay
		140 - 183	gray fine to coarse sand
		183 - 210	gray fine to coarse sand w/ clay
		210 - 223	gray fine to coarse sand
223 - 226	gray clay		
226 - 241	gray fine to coarse sand		
241 - 260	gray fine to med sand w/ clay		

WELL NO. <u>1 test well</u>	DIAMETER OF WELL <u>4"</u>	DEPT. OF WELL <u>283'</u>
HRS. PUMPED <u>2 1/2</u>	SLOT SIZE <u>.016</u>	TYPE OF CASING <u>PVC</u>
CAPACITY G.P.M. <u>50</u>	DRILLING MACHINE NO. <u>D-2</u>	LENGTH OF CASING <u>263'</u>
STATIC LEVEL <u>13'6"</u>	DRILLER <u>C. Wallace</u>	DISTANCE TO TOP OF SCREEN <u>263'</u>
PUMPING LEVEL <u>17'</u>	GRAVEL <u>2</u>	TYPE SCREEN <u>PVC</u>
SPECIFIC CAPACITY <u>13</u>	BAGS OF CEMENT <u>3</u>	SIZE OF SCREEN <u>4"</u>
PUMPED WITH <u>air-pumper</u>	DATE WELL COMPLETED <u>8-12-87</u>	
DEPTH OF CEMENT GROUT <u>0-20</u>	DRILLER'S HELPER <u>R. Horsey</u>	
DEPTH GRAVEL PACKED <u>250-295</u>		<u>Calvin Wallace</u> WELL DRILLER'S SIGNATURE