## STATE OF DELAWARE **DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAYS**

F.A. Project: S.R. 26, Atlantic Avenue from Clarksville to Assawoman Canal

Contract: 24-112-10

Boring Location: Sta. 57+00, 20' Rt. C.L.

**Boring Surface Elev.:** 

Reference:

Wt. of Casing Hammer:
Wt. of Sample Hammer: 140
Type of: D-Sampler: Split
S-Sampler:
U-Sampler:
Core Blt: Average Fail: Average Fail: O.D. of Sampler: O.D. of Samp. Tube: O.D. of Samp. Tube: O.D. of Rock Core: Lbs. IN. IN. IN. IN. Lbs. 30 Split-Barrel O.D. O.D. Ō.D. O.D.

Casing Size: 3 1/4"
Hollow Stem Auger:

From Depth of: From Depth of: Inches

0.0

Water Level Readings Date

Time 11:00 a.m.

Depth of Hole 6.0

Depth of Casing 4.0'

Depth of Water 4.5

To: To:

Elev. of Water -4.5

8.0

Ft.; Ft.;

Dia. U-Sample Boring: U-Samples:

Ft. Ft.

6.01

Boring No.: RB#29

Pay Quantities: 2 1/2 in. Dia. Dry Sample Boring: No. of 2 in. Dia. Shelby Tubes: 2 1/2 in. Dia. Contin. Sample Boring:

Boring Contractor: Walton Corporation

**Driller:** Dave Burt

Helpers: Jason Truver & Wayne Hurd

Q:22-29

No. of:

Core Drilling in Rock:

Depth	Daily Progress	No.	Sample Depth	Blows/6"	Sample Description Class./G.I. Remarks	
(ft.)			Depth 2.0'		OCCUPANTS.	
3		'	2.0	2 3 7 6	Moist medium dense brown silty fine to Coarse sand w/trace of gravel.  A-2-4(0)	
				6	coase said widace of graver.	
			4.0'		14" RECOVERY	
		2	4.0'	2 5 5 4	Moist loose brown silty fine to coarse sand A-2-4(0)	
			]	5 4	w/trace of gravel.	
	i					
6		3	6.0' 6.0'	3	24" RECOVERY	
		3	0.0	3 3 3	Wet loose gray fine sand w/some clay,  trace of coarse sand.  A-2-4(0)	
				3	trace of coarse said.	
<u> </u>			8.0'		24" RECOVERY	
		4	8.0'	3 3 3 4	Saturated loose grayish brown silty fine A-2-4(0)	
9				3 4	sand w/trace of coarse sand.	
				:		
			10.0'		23" RECOVERY	
			[			
12						
				ĺ		
			ŀ		+	
$\vdash \vdash \vdash$						
15						
13						
18						

Remarks:

Reviewed By:	Soils Supervisor:

## **KEY TO SYMBOLS**

Symbol Description

Strata symbols

10	•	-1	Е	•	а

Silty sand



Sand

## Notes:

- 1. Exploratory borings were drilled on 5-11-2006 using a 3 1/4-inch diameter hollow stem auger.
- No free water was encountered at the time of drilling or when re-checked the following day, unless recorded on 1st page.
- 3. Boring locations were taped from existing features and elevations extrapolated from survey unless otherwise reported.
- 4. These logs are subject to the limitations, conclusions, and recommendations in this report.
- 5. Results of tests conducted on samples recovered are reported on the logs.