STATE OF DELAWARE **DEPARTMENT OF TRANSPORTATION** DIVISION OF HIGHWAYS

		DIVIDION OF THOMAS	
F.A.	Project:	S.R. 26, Atlantic Avenue from Clarksville to Assawoman Canal	Boring No.: SB # 57

Contract: 24-112-10

Boring Location: Sta. 116+65, 45' Rt. C.L.

Boring Surface Elev.:

Reference:

Wt. of Casing Hammer: Wt. of Sample Hammer: Type of: D-Sampler: S-Sampler: U-Sampler:	I40 Split-barrel	Lbs. Lbs. O.D. O.D. O.D.	Average Fall: Average Fall: O.D. of Sampler: O.D. of Samp. Tube: O.D. of Samp. Tube:	30 2	IN. IN. IN. IN. IN.
Core Bit:		Q.D.	O.D. of Rock Core:		IN.

Casing Size: 5 1/7 Hollow Stem Auger:

Inches

From Depth of: From Depth of:

0.0'

34.0

Water Level Readings Date 5/9/2006

Time 9:00 a.m. Depth of Hole 5.5'

Depth of Casing 4.0

Depth of Water 4.0'

To: To:

Elev. of Water -4.0

35.51

Ft.;

Dia. U-Sample Boring: U-Samples:

Ft.

Pay Quantities: 2 1/2 in. Dla. Dry Sample Boring: No. of 2 in. Dla. Shelby Tubes: 2 1/2 in. Dla. Contin. Sample Boring:

Ft.;

No. of: Core Drilling in Rock:

Ft.

Boring Contractor: Walton Corporation Driller: Dave Burt

Helpers: Jason Truver & Wayne Hurd

Q134-66

Depth (ft.)	Daily Progress	No.	Sample Depth	Blows/6"	Sample Description	Class./G.I.	Remarks
3		1	2.0'	2 2 3 3	Wet loose brown silty fine to coarse sand w/trace of gravel.	A-2-4(0)	
			4.0'		20" RECOVERY		
6		2	5.5' 7.0'	W/H 2 2	Saturated very loose gray fine to coarse sand w/trace of silt. 10" RECOVERY	A-3	
9							
12		3	10.5' 12.0'	1 1 2	Saturated very loose brown fine to coarse sand w/some silt, trace of gravel. 16" RECOVERY	A-2-4(0)	
18		4	15.5' 17.0'	2 1 2	Saturated very loose brown fine sand w/ some silt and coarse sand, trace of gravel. 16* RECOVERY	A-2-4(0)	

Remarks:

Reviewed By:	Soils Supervisor:	

STATE OF DELAWARE **DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAYS**

F.A. Project: S.R. 26, Atlantic Avenue from Clarksville to Assawoman Canal Contract: 24-112-10

Boring No.: SB # 57

Depti	Depth Daily No. Sample Blows/6" Sample Description Class./G.I. Remarks					Remarks		
(ft.)	Progress	No.	Sample Depth	Riows/6"		Sample Description	3,003,70.1.	
	_							
21		5	20.5'	3 2 3		Saturated loose brown fine to coarse sand w/some silt, trace of gravel. 18" RECOVERY	A-2-4(0)	
27		6	25.5' 27.0'	2 3 3 3		Saturated loose brown fine to coarse sand w/some silt. 18" RECOVERY	A-2-4(0)	
30		7	30.5'	2 3 3 3	_	Saturated loose brown fine sand w/some silt and coarse sand, trace of gravel. 18" RECOVERY	A-2-4(0)	
33		8	35.5'	2 2 2 5 5		Saturated loose brown fine to coarse sand	A-2-4(0)	
3			37.0	1		w/some silt, trace of gravel. 18" RECOVERY		
.h.	15							

KEY TO SYMBOLS

- 1 -	_		
Symbol	Desc	grin	tion

Strata symbols

-	_	_	_	_	_	_
11	•		•	•		

Silty sand



Sand

Notes:

- Exploratory borings were drilled on 5-9-2006 using a 3 1/4-inch diameter hollow stem auger.
- No free water was encountered at the time of drilling or when re-checked the following day, unless recorded on 1st page.
- 3. Boring locations were taped from existing features and elevations extrapolated from survey unless otherwise reported.
- 4. These logs are subject to the limitations, conclusions, and recommendations in this report.
- 5. Results of tests conducted on samples recovered are reported on the logs.