DELAWARE GEOLOGICAL SURVEY UNIVERSITY OF DELAWARE NEWARK, DELAWARE

Qj32**–1**6

WELL COMPLETION REPORT

E (ler's Log

PLEASE SUBMIT THIS REPORT WITHIN 30 DAYS AFTER COMPLETION OF THE WELL

WELL LOG State the kind of formations penetrated, their depth, their thickness, and if water-bearing		CASING AND SCREEN RECORD State the kind and size of casing, liner, shoe, screen and other accessories (if no casing used, give diameter of well)			National Guard
					Owner
					Address
	,	give didinater of wer		I	Bethany Beach
	Foot		Dicm.	Feet	
	From To			From To	Tenant
	•				
					Address
Fill	0-8				·
	0.00				
gray, silty clay	820				(Please draw location of well and road sketch on reverse side)
	מס מד				
same with a lot of	20-25				pumping test
shells					Hours Pumped
e	מל של				Pumping rate GPM
fine and coarse gray	25-35	•	1		Tumping rate
sand with shells,					WATER LEVEL
clayey					Distance from land surface to water:
	35-52				Before Pumping ft.
sandy lt. gray clay	35 - 52				
and clayey fine sand					After Pumping ft.
Pina to compa	52-80				APPEARANCE OF WATER
very fine to coarse) 2 = 00				Clear
sand					Cloudy
sh marr allor	80-89				
sh gray clay	00-09				Taste
were fine to were acc	nce				Odor
very fine to very coa	89-130				
white sand and very	09-150				Height of casing above land surface ft.
small gravel					
same with some silty	130-215		٠,		PUMP
-	150-215		,		Туре
gray clay					Capacity—GPM
very fine to very	215-235				GPHr
-	21/-2//				Pump column length ft.
coarse lt. gray sand					
very fine to coarse	235-242				REMARKS
lt. gray sand	277-245	,			
ros graj cana					
					•
			ļ		
		1			
	!				
<u> </u>	1		1		· ·
		1		ļ]
				1	Date well completed
•					Well Driller
•					Signature
	1	1	1	1	