Delmarva Drilling Co., Inc. Pd4/-/

P. O. BOX 188

BRIDGEVILLE, DELAWARE 19933

Water Well Contractors

CUSTOMERTown of Delmar JOB_D						
ADDRESS Delmar, Delaware					DATE 9-17-80	
L OCATION	851 No	orth of Foske	y Lane	, 163' West of Railroad	tracks	
FEET FROM GRO SURFACE O TO		, we		LL LOG		
G ROUND		0-1		Top soil		
1		1-12		Fine to medium tan sand with yellow clay layers		
Ť		12-22		Fine to coarse tan sand		
		22-37		Fine to coarse brown sand and iron ore		
TOTAL DEPTH . FT.		37-39		Gravel and iron ore		
	166	39-61 .		Fine to coarse tan sand		
	9	61-98		Fine to coarse brown sand and gravel		
		98-103		K Gravel and blue clay		
		103-117		Blue clay with fine sandw/some clay shigers		
	∢ C AS ING >	117-155		Fine to medium gray sand		
		155-168		Fine to medium gray sand w/gray clay		
		168-208		Fine to coarse gray sand		
		2C8-212		Fine to medium gray sand w/clay layers		
'	1					
	2					
₩ .	5				Transport	
Ţ	1			· · · · · · · · · · · · · · · · · · ·		
WELL NO. 6" test well DIAME			DI AMETE	R OF WELL 6"	DEPT, OF WELL 200'	
HRS. PUMPED 6 SLOT SI				ze016	TYPE OF CASING PVC	
CAPACITY G.P.M. 40 DRILL				IG MACHINE NO. D3	LENGTH OF CASING 166'	
STATIC LEVEL 13'5" DRIE			DRILLER	Kelley & Cowgill	DISTANCE TO TOP OF SCREEN 166-200'	
PUMPING LEVEL 17'5" GRAVE				#2	TYPE SCREENPVC	
SPECIFIC CAPACITY 10 BAGS				CEMENT 12	SI ZE OF SCREEN6"	
PUMPED WITH DUMDET DATE				LL COMPLETED 9-18-80		
				's HELPER Myer & Wallace	Kelley & Cowgill	
DEPTH GRAVE	L PACKED	_147=200'		·	WELL DRILLER'S SIGNATURE	