miller Cittain	PUMP MANUFACTURE	NII+	
	RATED CAPACITY (GPM)	414	
NDAR 8-10-85	PUMP INTAKE SETTING A	FT. BELO	W GRADE
TEST PERMANENT		PLETED WELL	
	15001		YES NO
ESTIC EL AGRICULTURAL	A AT LEAST 15' FROM ANY FOL	NOITADNU	9 0
CIAL INDUSTRIAL	B. AT LEAST 50' FROM ANY SEPTIC TANK		
ATION D PUBLIC	C AT LEAST 10' FROM TOWN SEWER LINE		
ITOR DEWATERING	D. AT LEAST 100' FROM THE !	NEAREST EDGE	
PUMP RECHARGE HEAT PUMP SUPPLY	OF ANY TILE FIELD		
FR (Specify)	THE NEAREST NE		
ACEMENT WELL? YES IN NO E	SEPTIO TILE FIELD CES	SPOOL OR PE	RIVY
T DATE FOR OLD WELL	FROM COMPLETED WELL.		
T METHOD	IS COMPLETED WELL LOCATED AS SHOW!!		
DDILLING METHOD	ON APPLICATION FORM?		
DRILLING METHOD DISCRED DISCRED CABLE TOOL	IF NO, DESCRIBE LOCATION O	HANGE OR OTH	ER COMMENTS.
☐ JETTED ☐ CABLE FOOL		↑ . <u>~</u>	
RY D REVERSE D WASHED	Ki33-07		
ecity)			91
DRILLED	B	0 20 6	
United States	n B G B	U V is	
CASING SEQUENCE	לעון		
INNER OUTER	WATER SUPPLY		
1811			
ом <u>37'</u>			
ITER S"			
RIAL WC	VALLI	001112	
SCREEN SEQUENCE			
INNER CUTER			
CIM US'			
VIVI	DRILLERS LOG DESCRIPTION	IOP OF STRATA	BOTTOM OF STRATA
RIAL DVC	top soil	0	1
WHITTEN APPROVAL FOR SCREENING!	· ·	•	
GRAVEL PACKING MOTE THAIR OME ACU- IFER MUST BE OSTAINED FROM DWINEC	F. tan sand w/clay	1	5
CEMENT [] BENTONITE CLAY	tan f/m sand	5	16
OCIVICIA DE BENTONITE OCA, LE	white f/m sand	16	26
		~~	
ACKFILL OF WELL ANNULUS	tan f/c sand w/grav	26	61
FROM TO FEET			
TYPE #3			
TO CO FEET			
PLEVEL DATE 8-10-88			
ow. above) GROUND SURFACE			
ER LEVEL: T BELOW GRADE		<u> </u>	
HOURS AT JU GPM.	<u> </u>		
) COMPLETION:			
S ADAPTOR ID	PAGE 1 OF PAGES COMPANY NAME PHILIPPUL DO LUCIL SUSK MUCH		
NACOUE OD DE			
3 ABOVE GRADE	SIGNATURE OF ERELER IN C	topologic <u>e</u>	CATE
•	colum //al	<u> Lange</u>	2110184
		C COMPANIES AND CONTRACTOR OF THE PARTY O	Andrea and a second
18-75-01-03			·