Fo

STATE OF MARYLAND
DEPARTMENT OF GEOLOGY, MINES AND WATER RESOURCES
The Johns Hopkins University
BALTIMORE 18, MARYLAND

WELL COMPLETION REPORT

This report must be submitted within 30 days after completion of the well

WELL DESCRIPTION

WELL LOG

State the kind of formations penetrated, their depth, their thickness, and if water-bearing

	FEET from	FEET to
Clay	0	24
Slate Gray	24	343
Slate Brown	343	395
Slate & Shells	395	1140
Slate & Shells Brown	1140	1215
Slate & Shells Gray	1215	1860
Slate & Shells Lt. Brown	1860	1920
Brown Shale	1920	2105
Gray Shale	2105	2304
Brown Shale	2304	2442
Black Shale	2442	2570
Lime (Tully)	2570	2581
Black Shale	2581	2765
Lime (Tully)	2765	2780
Brown Shale	2780	2844
Gray Slate	2844	3010
Brown Shale	3010	3130
Black Shale	3130	3250
Lime - Light colored	3250	3272
Black Shale - Marcellus	3272	3325
Lime	3325	3328
Brown Break	3328	3331
Lime Onondaga	3331	3366
Chert Huntersville	3366	3424
Shale Needmore	3424	3520
Sand Oriskany	3520	3630
Lime	3630	3861

CASING AND SCREEN RECORD

State the kind and size of casing, liner, shoe, screen, and other accessories (if no casing used, give diameter of well)

DIAM. (inches)	FEET from	FEET to
Water: 20 ft., 610ft., 690 ft.		
Casing:		
13 3/8 OD set at 23'		
10 3/4 OD set at 296'		
Hole reduced to 8" at 1486'		
7 OD set at 3334'		
2 3/8 OD Tubing hung at 3396'		
Gas:		
3396' to 3402'- 327,000		
Acidized and increased to 435,000		
Shot 6/11/51 with 50 quarts from		
3390' to 3405' and increased to		
800,000		
Completed and turned into line 6/21/51		
T. D.		

Permit Number 7294

Name of Owner
Snee & Eberly

PUMPING TEST

Hours Pumped

Pumping Rate
Gallons per Minute

WATER LEVEL

Distance from land surface to water:

Before Pumping Ft.

When Pumping Ft.

APPEARANCE OF WATER

Clear

Cloudy

Taste

Odor

Height of Casing Above Land Surface Ft.

PUMP

Type

Capacity

Gallons per Minute

Gallons per Hour

Pump Column Length Ft.

REMARKS

Well Was Completed

Date 6/21/51

Well Driller John T. Johnst

Signature