

STATE OF MARYLAND
DEPARTMENT OF GEOLOGY, MINES AND WATER RESOURCES
 The Johns Hopkins University
 BALTIMORE 18, MARYLAND

WELL COMPLETION REPORT

This report must be submitted within 30 days after completion of the well

WELL DESCRIPTION					Permit Number <u>8924</u>
WELL LOG		CASING AND SCREEN RECORD			Name of Owner
State the kind of formations penetrated, their depth, their thickness, and if water-bearing		State the kind and size of casing, liner, shoe, screen, and other accessories (if no casing used, give diameter of well)			<u>Fox, Trimble et Al</u>
	FEET		DIAM. (inches)	FEET	PUMPING TEST
	from 0 to 15			from to	Hours Pumped.....
Soil	15 - 22				Pumping Rate Gallons per Minute.....
Sand	22 - 557	Water at 28 H.F.			WATER LEVEL
Lime	557 - 589	Casing	10"	347	Distance from land surface to water:
Slate	589 - 735				Before Pumping.....Ft.
Lime	735 - 865				When Pumping.....Ft.
Slate & Shells	865 - 975				APPEARANCE OF WATER
Lime	975 - 1100	Reduced hole at 1650			Clear.....
Slate & shells	1100 - 1230				Cloudy.....
Lime	1230 - 1520				Taste.....
Slate & shells	1520 - 1699				Odor.....
Lime	1699 - 1960				Height of Casing Above Land SurfaceFt.
Slate & shells	1960 - 2200				PUMP
Slate	2200 - 2250				Type.....
Slate & shells	2250 - 2420				Capacity
Lime	2420 - 2500				Gallons per Minute.....
Slate & shells	2500 - 2672				Gallons per Hour.....
Slate	2672 - 2800				Pump Column Length.....Ft.
Slate & shells	2800 - 3116				REMARKS
Dark Shale	3116 - 3373			
Gray Slate	3373 - 3518			
Black Slate	3518 - 3635			
Lime	3635 - 3643			
Black Slate	3643 - 3765	Casing	7" O.D.	3770	Well Was Completed
Lime	3765 - 3787				Date <u>May 3 1962</u>
Black Shale	3787 - 3817				Well Driller <u>L. H. Quigley</u>
Brown Break	3817 - 3823				<u>& Charlie Eddy</u>
Lime	3823 - 3852				Signature
Chert Sand	3852 - 3912	Show of gas, 17000 C.F.		3872	
Lime	3912 - 3940				
Slate	3940 - 3964				
Oriskany Sand	3964 - 4038	Gas & hole full of water		4038	
		Drove Lead Plug		3989	