

INTERVAL SHEET

Page 1

VDMR Well No.: 526

Date 9/13/61

Sample Interval: from 0 to 180

PROP: Ray Warrick #2

Total depth \_\_\_\_\_

COMP: Payne

Oil \_\_\_\_\_ Gas \_\_\_\_\_ Water X Exploratory \_\_\_\_\_

COUNTY: Albemarle (Crozet)

Cuttings X Core \_\_\_\_\_ Other \_\_\_\_\_

From-To	From-To	From-To	From-To	From-To
-	0-10	152-153	-	-
-	10-30	153-180	Not sufficient amount of material to	
-	30-40	-	-	- wash
-	40-42	-	-	-
-	42-51	-	-	-
-	51-57	-	-	-
-	57-60	-	-	-
-	60-62	-	-	-
-	62-68	-	-	-
-	68-75	-	-	-
-	75-79	-	-	-
-	79-82	-	-	-
-	82-87	-	-	-
-	87-90	-	-	-
-	90-97	-	-	-
-	97-99	-	-	-
-	99- <u>102</u>	-	-	-
-	102-104	-	-	-
-	104-105	-	-	-
-	105-106	-	-	-
-	106-107	-	-	-
-	107-110	-	-	-
-	110-112	-	-	-
-	112-118	-	-	-
-	118-128	-	-	-
-	128-132?	-	-	-
-	132-137	-	-	-
-	137-139	-	-	-
-	139-144	-	-	-
-	144-152	-	-	-

COMMONWEALTH OF VIRGINIA  
DEPARTMENT OF CONSERVATION AND ECONOMIC DEVELOPMENT

DIVISION OF MINERAL RESOURCES

Box 3667, University Station, Charlottesville, Virginia

WWCR 787  
VDMR 526

WATER WELL COMPLETION REPORT

OWNER: Ray Warrick Mailing Address: \_\_\_\_\_

TENANT: \_\_\_\_\_ Mailing Address: \_\_\_\_\_

DRILLER: Farwell (Roark) used a 71 machine Mailing Address: \_\_\_\_\_

WELL LOCATION: County Albemarle Approx. 2 <sup>mi</sup> miles

N. or underpass (direction) of Crozet and in direction of White Hall Cross Roads(?)

(Give direction and distance in feet or tenths of mile from two reference points - roads, towns, rivers, etc. - on county highway or other map.)

**WATER CONDITIONS**

**DEPTH**

STATIC WATER LEVEL 35

WATER ZONES (fissures or formations supplying water)

360 (from) ft. \_\_\_\_\_ (to) \_\_\_\_\_ (from) \_\_\_\_\_ (to) \_\_\_\_\_  
ft. \_\_\_\_\_, \_\_\_\_\_ ft. \_\_\_\_\_

**QUANTITY OF WATER**

WELL PUMPED (or bailed) at 25+ Gal. per Min. with 48 feet DRAWDOWN after \_\_\_\_\_ HOURS PUMPING.

FLOW (natural) \_\_\_\_\_ G.P.M. HEAD \_\_\_\_\_ ft. (above ground) **W**

REMARKS: \_\_\_\_\_

**QUALITY OF WATER**

COLOR \_\_\_\_\_ TASTE \_\_\_\_\_

ODOR \_\_\_\_\_ OTHER \_\_\_\_\_

ANALYSIS: AVAILABLE - Yes  No  ATTACHED Yes  No

TEMPERATURE \_\_\_\_\_

\_\_\_\_\_ WATER (from) \_\_\_\_\_ ft. \_\_\_\_\_ (to) \_\_\_\_\_ ft.  
(salt, brackish, iron, sulfur, acid, other)

USE OF WATER: Domestic  Town  Industry  Farm  Public  **S**

**CONSTRUCTION**

RIG TYPE (or method) \_\_\_\_\_  
(rotary, cable, bored, driven, etc..)

DATE: Started \_\_\_\_\_; Completed Apr. 17?, 1947

TOTAL DEPTH 370 ? ft.

BEDROCK at \_\_\_\_\_ ft.

**GROUTING INFORMATION**

METHOD USED \_\_\_\_\_

GROUTING MATERIAL \_\_\_\_\_

DEPTH OF GROUTING \_\_\_\_\_

**HOLE SIZE**

(diam) \_\_\_\_\_ in. (from) \_\_\_\_\_ ft. (to) \_\_\_\_\_ ft.

6 \_\_\_\_\_ 0 \_\_\_\_\_ 370

**CASING SIZE**

(diam) \_\_\_\_\_ in. (from) \_\_\_\_\_ ft. (to) \_\_\_\_\_ ft.

**SCREEN (or perforations)**

(diam.) \_\_\_\_\_ (from) \_\_\_\_\_ (to) \_\_\_\_\_ (opening size)  
in. \_\_\_\_\_ ft. \_\_\_\_\_

**PUMP (installed)**

TYPE \_\_\_\_\_ Cap. (gpm) \_\_\_\_\_

H.P. \_\_\_\_\_ Depth of intake \_\_\_\_\_ ft.

REMARKS: Test pump intake at 109' (capac. of pump 25 gpm) p. level was 83'; 18 hr. test, bigger test pump.

Source of information - Sydnor

Log of well (over)



Ab

J

1787

COMMONWEALTH OF VIRGINIA  
DEPARTMENT OF CONSERVATION AND ECONOMIC DEVELOPMENT

Sycnor

DIVISION OF MINERAL RESOURCES

Box 3667, University Station, Charlottesville, Virginia

W-526

WATER WELL COMPLETION REPORT

OWNER: Ray Warrick Mailing Address: \_\_\_\_\_

TENANT: \_\_\_\_\_ Mailing Address: \_\_\_\_\_

DRILLER: Farwell (Roark) (used a 71 machine) Mailing Address: \_\_\_\_\_

WELL LOCATION: County Albemarle Approx. 2 miles N  
N. or underpass of at Crozet and in direction of White Hall Cross-Rds(?) of \_\_\_\_\_

(Give direction and distance in feet or tenths of mile from two reference points - roads, towns, rivers, etc. - on county highway or other map.)

WATER CONDITIONS

DEPTH

STATIC WATER LEVEL 35

WATER ZONES (fissures or formations supplying water)

(from) ? (to) \_\_\_\_\_ (from) \_\_\_\_\_ (to) \_\_\_\_\_  
 ft. \_\_\_\_\_, ft. \_\_\_\_\_  
 ft. \_\_\_\_\_, ft. \_\_\_\_\_

QUANTITY OF WATER

WELL PUMPED (or bailed) at 25+ Gal. per Min. with

48 feet DRAWDOWN after \_\_\_\_\_ HOURS PUMPING.

FLOW (natural) \_\_\_\_\_ G.P.M. HEAD \_\_\_\_\_ ft. (above ground) **W**

REMARKS: \_\_\_\_\_

QUALITY OF WATER

COLOR \_\_\_\_\_ TASTE \_\_\_\_\_

ODOR \_\_\_\_\_ OTHER \_\_\_\_\_

ANALYSIS: AVAILABLE-- Yes  No  ATTACHED Yes  No

TEMPERATURE \_\_\_\_\_

WATER (from) \_\_\_\_\_ ft. (to) \_\_\_\_\_ ft.  
(salt, brackish, iron, sulfur, acid, other)

USE OF WATER: Domestic  Town  Industry  Farm  Public

CONSTRUCTION

RIG TYPE (or method) (rotary, cable, bored, driven, etc.) \_\_\_\_\_

DATE: Started \_\_\_\_\_; Completed Apr. 17, 1947

TOTAL DEPTH 370? ft.

BEDROCK at \_\_\_\_\_ ft.

GROUTING INFORMATION

METHOD USED \_\_\_\_\_

GROUTING MATERIAL \_\_\_\_\_

DEPTH OF GROUTING \_\_\_\_\_

HOLE SIZE

(diam) \_\_\_\_\_ in (from) \_\_\_\_\_ ft (to) \_\_\_\_\_ ft (diam) \_\_\_\_\_ in (from) \_\_\_\_\_ ft (to) \_\_\_\_\_ ft

6 in 0 ft 370 ft

CASING SIZE

SCREEN (or perforations)

(diam.) \_\_\_\_\_ in (from) \_\_\_\_\_ ft (to) \_\_\_\_\_ ft (opening size)

PUMP (installed)

TYPE \_\_\_\_\_ Cap. (gpm) \_\_\_\_\_

H.P. \_\_\_\_\_ Depth of intake \_\_\_\_\_ ft.

REMARKS: Test pump intake at 109' (capac. of pump 25 gpm)  
p. level was 83'; 18 hr test; biggest test pump  
required