

VIRGINIA DIVISION OF MINERAL RESOURCES

Box 3667, Charlottesville, VA 22903

INTERVAL SHEET

C-184

~~3572~~

Page 1 of 1

Well Repository No:

Date rec'd: 3/27/72 Date Processed: 8/9/72

Sample Interval: from 0 to 560'

PROPERTY: Carter Bell

Number of samples: 55

COMPANY: R. L. Magette

Total Depth: 562'

COUNTY: Naussemond

Oil or Gas: Water: Exploratory:

From-To	From-To	From-To	From-To
0 - 10	250 - 260	500 - 510	-
10 - 20	260 - 270	510 - 520	-
20 - 30	270 - 280	520 - 530	-
30 - 40	Missing	530 - 540	-
40 - 50	290 - 300	540 - 550	-
50 - 60	300 - 310	550 - 560	-
60 - 70	310 - 320	-	-
70 - 80	320 - 330	-	-
80 - 90	330 - 340	-	-
90 - 100	340 - 350	-	-
100 - 110	350 - 360	-	-
110 - 120	360 - 370	-	-
120 - 130	370 - 380	-	-
130 - 140	380 - 390	-	-
140 - 150	390 - 400	-	-
150 - 160	400 - 410	-	-
160 - 170	410 - 420	-	-
170 - 180	420 - 430	-	-
180 - 190	430 - 440	-	-
190 - 200	440 - 450	-	-
200 - 210	450 - 460	-	-
210 - 220	460 - 470	-	-
220 - 230	470 - 480	-	-
230 - 240	480 - 490	-	-
240 - 250	490 - 500	-	-

unwashed only.

R
P

W-3572
C-184

R. L. MAGETTE COMPANY

Water Supply Contractor — Smithfield, Virginia

LOG OF WELL For Carter Bell
 Located at 7 - 11 Store in BLINTON CRITENDEN Nansemond County, State Virginia
 Date Drilling Started February 23, 1972, 19 Date Started 19
 Finished Drilling March 6, 1972, 19 Finished 19

FORMATION AND DEPTH OF WELL					DIMENSIONS OF CASING AND SCREEN						
TOTAL DEPTH OF ALL STRATA		DEPTH OF EACH STRATUM		FORMATION FOUND AT EACH STRATUM	TOTAL LENGTH OF ALL SCREENS AND CASINGS		LENGTH OF EACH SEC. OF SCREEN OR CASING		SPECIFY SCREEN OR CASING	SIZE OF SCREEN OR CASING	GUAGE OF SCREEN
FT.	IN.	FT.	IN.		FT.	IN.	FT.	IN.			IN.
Driller's Log											
0	-	7		Top soil & red sandy clay							
7	-	18		Red clay							
18	-	26		Course red sandy							
26	-	54		Sand & shell							
54	--			Shell & fine sand							
71	-	83		Blue clay & shell							
83	-	226		Blue clay							
226	-	260		Very fine white sand							
260	-	314		Brown clay							
314	-	363		Very fine sand & limestone layers							
363	-	395		Black sand (gloucnite)							
395	-	440		Sticky red clay							
440	-	478		Fine sand & clay							
478	-	529		Fine sand w/streaks of clay							
529	-	562		Water bearing sandw/mica							

W-3572